

## JKL PART NO.: CF20305-24B

JKL LAMP PART NO.	COLOR WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) (AVG.)	
CF20305-24B x = 0.278±0.01 y = 0.264±0.01			780	5	42,000 TYP.	40,000	

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OFTHE INITIAL RATING.

		METRIC	DIMENSIONS ARE	1	IVI	ſ				
		$\Rightarrow \neg$	TOLERANCE UNLESS	Ľ		COMPON	NENTS COR	PORAT	ION	
		1	⊕−€−	OTHERWISE SPECIFIED 1 PL +/- 0.2	TITLE	MIN	IATURE COL	CATHODE		
			THIRD ANGLE PROJECTION	2 PL +/- 0 ANGLE +/- 0		FLU	ORESCENT L	AMP		
			DRAWN BY	APPV'D BY DATE	SIZE	FSCM NO.				
Α	START VOLTS TO 2600 & OPER. VOLT TO 1400	8/23/07	L. WENGSTROM	L.R. 8/28/07	Α	55335	<sup>NO.</sup> CF	20305-24B		
	RELEASED	11/10/05	- CAD DRAWING -		SCALE	1	RELEASED	REVISION	REV.	SHEET
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	MANUAL REVISIONS NOT PERMITTED			NONE	DATE 11/10/05	DATE 8/28/07	NO A	1 <sub>OF</sub> 1

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for CCFL Fluorescent Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below :

 BF20170-38B
 BF4142-20B
 BF20137-26B
 BF2698-20B
 CF20228-31B
 CF26349-28B
 BF22140-24B
 BF22180-28B
 BF26180-24B
 BF5118 

 20B
 BF2698-31BASSY
 BF20125-28B
 BF20325-24B
 BF26214-20B
 BF26230-24B
 BF26250-24B
 BF2661-24B
 BF386-20B

 BF20218-24B
 BF20226-24B
 BF20292-24B
 BF22258-25B
 BF22312-45B
 BF26318-20B
 BF3100-20B
 BF3228-21B
 BF5165-20B
 CF20305 

 24B
 BF3300-20B
 BF350-20B
 BF350-20B
 BF350-20B
 BF350-20B
 BF350-20B