

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE	
E6522	6.0	.030	.025	0.31	10,000	C-2V	
E79	6.0	.200	.600	7.54	1,000	C-2R	
E84	6.3	.040	.030	0.38	20,000	C-2V	
E86	6.3	.200	.400	5.03	20,000	C-2V	
E12522	12.0	.030	.045	0.57	10,000	C-2F	
E21203A	12.0	.100	.640	8.04	2,000	C-2V	
E73	14.0	.080	.300	3.77	15,000	C-2V	
E37	14.0	.090	.500	6.29	1,500	C-2F	
E74*	14.0	.100	.720	9.05	1,000	C-2V	
E13522	24.0	.030	.160	2.01	5,000	C-2F	
E85	28.0	.040	.300	3.77	10,000	C-2F	
E17	28.0	.065	.650	8.17	5,000	C-2F	

*PRODUCTION CHANGE TO Pb FREE GLASS, CONTACT JKL FOR LOT IDENTIFICATION.

		METRIC	TOLERANCE UNLESS		COMPONENTS CORPORATION							ΓΙΟΝ	
			THIRD ANGLE PROJECTION	OTHERWIS 1 PL + 2 PL + ANGLE +	/- 0.20	TITLE	T-1 1/2	STAN	DARD (BLASS	WEDG	E BASI	E
Α	Pb FREE NOTE ADDED	8/25/04	DRAWN BY	APPV'D BY	•	SIZE A	FSCM NO. 55335		GLAS	S WE	GE B	ASE T	-1 1/2
REV. NO.	RELEASED & CANCEL GW-STD-T1 1/2 DESCRIPTION/ECO NUMBER	5/5/00 APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	NONE	RELEASE DATE	5/5/00	REVISION DATE	8/25/04	NO. A	1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Lamps category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

5AB 6180 8111 8623 912 120PS 1224 DE603 DW50 IFL-LX2162-16T C9A C9A 3015 303 19 PR13 268 GT-NE6H1225T

CM5004WW 32-2211T 509K 5314N1 5314N2 WWT1-EW10/GRN 4925H1 DW07 1141 MS25231-313 E73 CM2 7683EBP 8553

XE135B WWT2-EW34BLA 6S6/30V 7367 1301910036 7A1H 8630FBBB WT3F-20 85 106 105 BGF717-UV1 1974D 1495 373 400

502 67