

NOTES:

- 1. LED includes integrated diode for reverse voltage protection.
- 2. LED includes integrated resistor for current limiting.

Operating Temperature Range	-30°C to +85°C
Storage Temperature Range	-40°C to +100°C

TYPICAL ELECTRICAL & OPTICAL OPERATING CHARACTERISTICS (Ta = $25 \ \text{degree}$ C)

PART NUMBER	EMITTING COLOR	AMPERAGE mA	VOLTAGE Vdc	LUMENS	μW/cm ²	DOMINANT WAVELENGTH	VIEWING ANGLE DEGREES
LE-0503-03R	RED	15mA	12.0	0.70		630nm	20
LE-0503-03Y	YELLOW	15mA	12.0	0.70		595nm	20
LE-0503-03G	GREEN	15mA	12.0	2.00		525nm	20
LE-0503-03B	BLUE	15mA	12.0	0.70		470nm	20
LE-0503-03W	9000°K WHITE	15mA	12.0	2.50		x = 0.30 $y = 0.29$	20
LE-0503-03UV	ULTRA VIOLET	15mA	12.0		235	405	20

T-3 1/4 WEDGE BASE LED				
13				
To	DE\/	SHEET		
		1 1		
0/10/10		I OF I		
0	03	03		

DIMENSIONS ARE IN MILLIMETERS

METRIC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Replacement Lamps - Based LEDs category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

LAPD-1A LAPD-1R LAPD-2R LAPD-6W LSTD-M4S SSP-1156B153S12 SSP-1157B156U12 SSP-LXS110818BA 560-0101F 560-0103F LAPD-1W LAPD-6R 560-0104F 585-1113 SSP-LXC1283S24 SSP-3MB96U12G SLL-05EY 1.90.690.684/0000 560-0203F 586-2206-205F SSP-LXS1826U16A LATD-2JW 24LS4-G1 24LS4-R1 MF200-NFW5H MB403-W60-CW-BP 387LP-A 1819LS2-G-CG 387LP-R 387LP-B 387LP-W 387LP-G 6S6LS155-CWR 130MBLS-G-CG 5000404LAMP E10SB12A E10SB130A E10SB24A E10SG12A E10SG130A E10SG24A E10SR12A E10SR130A E10SR24A E10SR24A E10SR130A E10SR24A E10SR2