

## NOTES:

- 1. LED includes integrated diode for reverse voltage protection.
- 2. LED includes integrated resistor for current limiting.

OPERATING TEMPERATURE RANGE	-30°C to +85°C
STORAGE TEMPERATURE RANGE	-40° to +100°C

## TYPICAL ELECTRICAL & OPTICAL OPERATING CHARACTERISTICS (Ta = 25 degree C)

PART	EMITTING	AMPERAGE	VOLTAGE	LUMENS	DOMINANT	VIEWING ANGLE
NUMBER	COLOR	mA	Vdc		WAVELENGTH	DEGREES
LE-0509-01R	RED	15mA	24.0	1.00	630nm	95
LE-0509-01Y	YELLOW	15mA	24.0	1.00	595nm	95
LE-0509-01G	GREEN	15mA	24.0	2.00	525nm	95
LE-0509-01B	BLUE	15mA	24.0	1.00	470nm	95
LE-0509-01W	9000°K WHITE	15mA	24.0	2.00	x = 0.30 $y = 0.29$	95

C ADD 9000° WHITE 6/16/10 PROJECTION ANGLE +/- 0  C ADD 9000° WHITE 9/06/09 DRAWN BY APPLY BY DATE SIZE FSCM NO. DRAWING	
D   CHANGE CHART	
A UPDATE ON ELECTRICAL 8/11/08 L. WENGSTROM L.R. 5/16/10 A 55335 NO. LE-0509-01	
ENGR RELEASE & CANCEL PL-0509-01-1 TO -05 7/3/06 - CAD DRAWING - SCALE RELEASED REVISION REV.	SHEET
REV. DESCRIPTION/ECO APPV'D - CAD DRAWING - NO. NUMBER DATE MANUAL REVISIONS NOT PERMITTED NO. DATE 7/3/06 DATE 6/16/10 NO.	1 of 1

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Replacement Lamps - Based LEDs category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

LAPD-1A LAPD-1R LAPD-2R LAPD-6W LSTD-M4S SSP-1156B153S12 SSP-1157B156U12 SSP-LXS110818BA 560-0101F 560-0103F LAPD-1W LAPD-6R 560-0104F 585-1113 SSP-LXC1283S24 SSP-3MB96U12G SLL-05EY 1.90.690.684/0000 560-0203F 586-2206-205F SSP-LXS1826U16A LATD-2JW 24LS4-G1 24LS4-R1 MF200-NFW5H MB403-W60-CW-BP 387LP-A 1819LS2-G-CG 387LP-R 387LP-B 387LP-W 387LP-G 6S6LS155-CWR 130MBLS-G-CG 5000404LAMP E10SB12A E10SB130A E10SB24A E10SG12A E10SG130A E10SG24A E10SR12A E10SR130A E10SR24A E10SR24A E10SR130A E10SR24A E10SR2