

NOTES:

- 1. LED includes integrated diode for reverse voltage protection.
- 2. LED includes integrated resistor for current limiting.

TYPICAL ELECTRICAL & OPTICAL OPERATING CHARACTERISTICS (Ta = 25 degree C)

PART NUMBER	EMITTING COLOR	AMPERAGE mA	VOLTAGE Vdc	LUMENS	COLOR COORDINATES		
LE-0603-02R	RED	20mA	12.0	2.00	630nm		
LE-0603-02Y	YELLOW	20mA	12.0	2.00	595nm		
LE-0603-02G	GREEN	20mA	12.0	9.00	525nm		
LE-0603-02B	BLUE	20mA	12.0	2.00	470nm		
LE-0603-02W	WHITE	14mA	12.0	10.00	x = 0.29 $y = 0.28$		

		METRIC	DIMENSIONS ARE IN MILLIMETERS			K	Lcon	ЛРО N	NENTS C	'ORF	PORA	TION	
		\oplus	TOLERANG OTHERWISE 1 PI +/	SPECIFIED	IIIILE					OKI	OKA	TION	
D	CHANGE WHITE TO 14mA CHANGE DIA, TO 10.5 MAX.	12/8/10	THIRD ANGLE PROJECTION	2 PL +/- 0 ANGLE +/- 0			LED FESTOON LAMP						
B	CHANGE MOL TO 43.0 MAX.	1/22/09	DRAWN BY	APPV'D BY	DATE	SIZE	1	DRAWING					
Α	CHANGE CHARTS & ADD NOTES			L.R.	12/8 /10	Α	55335	NO. LE-0603-02					
	ENGR. RELEASE & CANCEL PL-0603-02-1 TO -5 7/5/06		- CAD DRAWING -		SCALE	1	RELEASED		REVISION		REV.	SHEET	
REV NO.			MANUAL REVISIONS NOT PERMITTED			NONE	DATE 7	7/5/06	DATE 12/8	8/10	NO. U	1 _{OF} 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Replacement Lamps - Based LEDs category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

LAPD-1A LAPD-1R LAPD-2R LAPD-6W LSTD-M4S SSP-1156B153S12 SSP-1157B156U12 SSP-LXS110818BA 560-0101F 560-0103F LAPD-1W LAPD-6R 560-0104F 585-1113 SSP-LXC1283S24 SSP-3MB96U12G SLL-05EY 1.90.690.684/0000 560-0203F 586-2206-205F SSP-LXS1826U16A LATD-2JW 24LS4-G1 24LS4-R1 MF200-NFW5H MB403-W60-CW-BP 387LP-A 1819LS2-G-CG 387LP-R 387LP-B 387LP-W 387LP-G 6S6LS155-CWR 130MBLS-G-CG 5000404LAMP E10SB12A E10SB130A E10SB24A E10SG12A E10SG130A E10SG24A E10SR12A E10SR130A E10SR24A E10SR24A E10SR130A E10SR24A E10SR2