



1. OPERATION

- 1. GENTLY LIFT LATCH AT SIDE OF CONNECTOR.
- SWING COVER OFF OF CONTACTS.
- 3. SLIDE THE FLEX TAPE INTO THE CONNECTOR PLACING THE EDGE OF THE FLEX TAPE UNDER 2 HOLD DOWN TABS. MAKE SURE THE POLARITY IS MATCHED BETWEEN THE FLEX TAPE AND THE CONNECTOR COVER.
- 4. FOLD OVER THE COVER AND PRESS IN PLACE UNTIL THE LATCH IS FULLY ENGAGED.
- 2. LIMIT CURRENT TO A MAXIMUM OF 5 AMPS.
- 3. WILL WORK WITH 10mm OR 12mm WIDE FLEX RIBBON.

JKL PART NO.: ZFS-CH0-12J

			METRIC	DIMENSIONS ARE IN mm (INCHES) TOLERANCE UNLESS		JKL COMPONENTS CORPORATION								
			THIRD ANGLE PROJECTION	OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/-		TITLE	NO SO	LEX						
/ `	ADD NOTE 3	10/8/13	DRAWN BY	APPV'D BY	DATE 10/8/13	SIZE A	FSCM NO.				CH0-12	 2J		
REV NO.	RELEASE & CANCEL PL-1206-01 DESCRIPTION/ECO NUMBER	3/5/13 APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	1	RELEASE DATE	^D 3/5/13	REVISION DATE	10/8/13	REV. A	۱ L	HEET OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Lighting Connectors category:

Click to view products by JKL manufacturer:

Other Similar products are found below:

293300-7 293660-5 CNX_H03_NTP 30-9767-BU 3605 3-21030-1 ZCH-110-RGB-I 503471-0290 ZCH-110-RGB-J 217-0716-200

1954563-1 1-293657-2 2834036-1 2834037-1 1-2213222-4 2-2213222-4 2213222-4 2834122-3 2834122-5 2834135-2 FLA-R4142-30

FLA-R4162-30 FLA-R2142-30 FLA-R2162-30 FLA-R2161-30 FLA-R0161-30 FLA-R0141-30 FLA-R0142-30 FLA-R0162-30 FLA-C00
00 DGA00010553 CNXV04NTP 104128-0610 503485-0000 (Cut Strip) 503485-0000 (Loose Piece) 503485-0000 (MINI Reel) 1-2834074-2

1-2834074-3 1357-AC PLUG W2C (CHINA) 1357-AC PLUG W2 (USA) 104266-0110 CNXV02NTP 2106212-1 2-2834074-2 104266
0210 293470-1 293651-2 293651-4 1-2834006-2 293651-1