SURFACE MOUNT MLCCs 10 - 200 VDC

	age								Av	'All	LAI	BLI	E (CA	PA	СП	AN	ICE	E (Co	DE									
JDI	Inches	(mm)	Voltage	0R5	XRX	100	120	150	180	220	270	330	390	470	560	680	820	101	121	151	181	221	271	331	391	471	561	681	821	102
R05	0201	(0603)																												
	L .024 ±.001 W .012 ±.001	(0.60 ±.03) (0.30 ±.03)	25V																											
-	T .012 ±.001	(0.30 ±.03)	16V	<u> </u>																										
	EB .006 ±.002	(0.15±.05)	10V																											
R07	0402 L .040 ±.004	(1005)	50V																											
	W .020 ±.004	(1.02 ±.10) (0.51 ±.10)	25V																											
-	T .025 Max. EB .008 ±.004	(0.64) (0.20±.10)	16V	-																								$\mid \mid \mid$		_
			10V																											
R14	0603 L .063 ±.008	(1608) (1.60 ±.20)	200V 100V																											
	W .032 ±.008	(0.81 ±.20)	50V	-					_										_											
-	T .035 Max. EB .010±.005	(0.89) (.25±.13)	25V																											
		()	16V	-					_										_											_
R15	0805	(2012)	200V																											
	L .080 ±.010	(2012) (2.03 ±.25)	100V																											
	W .050 ±.010	(1.27 ±.25)	50V																											
	T .050 Max. EB .020±.010	(1.27) (0.51±.25)	25V																											-
			16V																											
R18	1000	(2010)	200V																											
	1206 L .125 ±.010	(3216) (3.17 ±.25)	100V																											
	W .062 ±.010	(1.57 ±.25)	50V																											
	T .050 Max. EB .020 ±.010	(1.27) (0.51 ±.25)	25V																											_
S41	1210	(3224)	200V																											
	L .125 ±.010	(3.18 ±.25)	100V																				1	NPO)					
	W .095 ±.010 T .065 Max.	(2.41 ±.25) (1.65)	50V							~			\leq)	X7F	2					
	EB .020 ±.010	(0.51 ±.25)	25V						W		\times			Ľ,)	X5F	{					
			16V					Ĩſ	<					<u> </u>	\searrow	>														
S43	1812	(4532)	200V				T -	71						\geq	1	É – E	Е/В													
	L .175 ±.010 W .125 ±.010	(4.45 ±.25)	100V									Y																		
	T .085 Max.	(3.17 ±.25) (2.16)	50V										/																	
	EB .025 ±.015	(0.64 ±.38)	25V																											
				0R5	XRX	100	120	150	180	220	270	330	390	470	560	680	820	101	121	151	181	221	271	331	391	471	561	681	821	102

How To ORDER - SURFACE MOUNT MLCC

100	R 07	W	104	Κ	V	4	Ε
VOLTAGE	SERIES/SIZE	DIELECTRIC	CAPACITANCE	TOLERANCE	TERMINATION	MARKING	PACKING
100 = 10 V DC 160 = 16 V DC 250 = 25 V DC 500 = 50 V DC 101 = 100 V DC 201 = 200 V DC	R05 = 0201 R07 = 0402 R14 = 0603 R15 = 0805 R18 = 1206 S41 = 1210 S43 = 1812	N = NP0 W = X7R X = X5R	1st two digits are significant; third digit denotes number of zeros, R = decimal. SR6 = 5.6 pF 100 = 10 pF 102 = 1,000 pF 474 = 0.47 μ F	$\label{eq:states} \begin{array}{l} {}^{*}B=\pm 0.10 \ pF \\ {}^{*}C=\pm 0.25 \ pF \\ {}^{*}D=\pm 0.50 \ pF \\ F=\pm 1 \ \% \\ G=\pm 2\% \\ J=\pm 5\% \\ K=\pm 10\% \\ M=\pm 20\% \end{array}$ $\ \ \ \ \ \ \ \ \ \ \ \ \ $	V = Nickel Barrier with 100% Tin Plating (Matte) T = SnPb	3 = Special 4 = Unmarked 6 = EIA Code* *Not available on sizes ≤ 0402	E = Embossed 7" T = Punched 7" U = Embossed 13" R = Punched 13" No code = bulk Tape specifications on page 48. Not all tape styles are avail- able on all parts.



www.johansondielectrics.com

Part number written: 100R07W104KV4E

SURFACE MOUNT MLCCs 10 - 200 VDC

									A	۱ <i>v</i> /	NL,	AB	LE	С	AP.	AC	IT/		CE	С	CO	E										age	CASE					
122	152	182	222	272	332	392	472	562	822	103	123	153	183	223	273	333	473	563	683	823	104	224	334	474	105	225	335	475	106	476	107	Voltage	Case Size					
																						1	NPO) C								25V	0201					
)	X7F	7								16V	R05					
)	X5F	7								10V						
																																50V						
																																25V	0402					
																																16V	R07					
																																10V						
																																200V						
																																100V	0603					
																																50V	R14					
																																25V	n14					
																																16V						
																																200V	_					
																																100V	0805					
																																50V	R15					
																														Hig		25V	1110					
																														Serie		16V						
																									TC	or v	aiu	es 2	≥ 1	.0µ	F	200V	1000					
																																100V	1206					
																																50V	R18					
																																25V						
							<u> </u>															_										200V						
_																																100V	1210					
_																																50V	S41					
	_						_		-												_											25V	-					
-	_																															16V						
_	_																															200V	1812					
	_																															100V 50V	S43					
-							\vdash																									25V	343					
	2	2	2	2	~	2	~	2	~	<i>с</i>	<i>с</i> о	с С	<u>ო</u>	<i>с</i>	4	4	4	4	5	5	2	5	9	9	2	201												
122	152	182	222	272	332	392	472	562	822	103	123	153	183	223	273	333	473	563	683	823	104	224	334	474	105	225	335	475	106	476	107							

ELECTRICAL CHARACTERISTICS

Please refer to page 78 of the catalog or www.johansondielectrics.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multilayer Ceramic Capacitors MLCC - SMD/SMT category:

Click to view products by Johanson manufacturer:

Other Similar products are found below :

D55342E07B523DR-T/R NCA1206X7R103K50TRPF NCA1206X7R104K16TRPF NIN-FB391JTRF NIN-FC2R7JTRF NMC0402NPO220J50TRPF NMC0402X5R105K6.3TRPF NMC0402X5R224K6.3TRPF NMC0402X7R103J25TRPF NMC0402X7R153K16TRPF NMC0603NPO330G50TRPF NMC0603NPO331F50TRPF NMC0603X5R475M6.3TRPF NMC0805NPO220J100TRPF NMC0805NPO270J50TRPF NMC0603NPO681F50TRPF NMC0805NPO820J50TRPF NMC0805X7R224K25TRPF NMC1206X7R102K50TRPF NMC1210Y5V105Z50TRPLPF NMC-H0805X7R472K250TRPF NMC-L0402NPO7R0C50TRPF NMC12063NPO2R2B50TRPF NMC-Q0402NPO8R2D200TRPF C1206C101J1GAC C1608C0G2A221J C1608X7R1E334K C2012C0G2A472J 2220J2K00562KXT KHC201E225M76N0T00 1812J2K00332KXT CCR06CG153FSV CDR14BP471CJUR CDR31BX103AKWR CDR33BX683AKUS CGA2B2C0G1H010C CGA2B2C0G1H040C CGA2B2C0G1H050C CGA2B2C0G1H060D CGA2B2C0G1H070D CGA2B2C0G1H120J CGA2B2C0G1H151J CGA2B2C0G1H07C CGA2B2C0G1H050C CGA2B2C0G1H390J CGA2B2C0G1H391J CGA2B2C0G1H3R3C CGA2B2C0G1H680J CGA2B2C0G1H6R8D CGA2B2C0G1H820J