

SPECIFICATIONS Current Rating: 1A AC,DC

Voltage Rating: 100V AC,DC Temperature Range: -25°C ~ +85°C Contact Resistance: 20mΩ Max. Insulation Resistance: $500M\Omega$ Min. Withstanding Voltage: 500V AC/minute Material: Nylon 66,UL94V-0

Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions			
	Α	В		
A1500H-02P	1.50	4.50		
A1500H-03P	3.00	6.00		
A1500H-04P	4.50	7.50		
A1500H-05P	6.00	9.00		
A1500H-06P	7.50	10.50		
A1500H-07P	9.00	12.00		
A1500H-08P	10.50	13.50		
A1500H-09P	12.00	15.00		
A1500H-10P	13.50	16.50		
A1500H-11P	15.00	18.00		
A1500H-12P	16.50	19.50		
A1500H-13P	18.00	21.00		
A1500H-15P	21.00	24.00		

			JOINT TECH ELECTRONIC IND. CO., LTD.							
			JOY DAY INDUSTRIAL CO., LTD.							
			UNIT SCALE SHEET		SHEET	TITLE:				
			mm 1 of 1		1 of 1					
			DRAWN BY		APP	ROVED BY	4 FO DITCH			
			董正一		-	董正一	1.50mm PITCH			
			2001.02.01 2001.02.01		1.02.01	HOUSING				
B2	REVISE	2007.10.25	GENERAL TOLERANCE		ANCE	113031110				
B1	REVISE	2007.10.16	X.X±0.25		ANG	LE±				
BO	NEW RELEASE	2006.07.07	X.XX±0.15 X.XXX±0.05		4	⊕	DRAW NO.:	REV.		
REV.	DESCRIPTION	DATE				Ψ	A1500H-XP	B2		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Joint manufacturer:

Other Similar products are found below:

571763P 58098-0628 61-168618-12P D38999/20FJ29SB L/C 72.250.1628.2 72.250.2428.2 74720-0505 747680210 76.350.0729.0 768711403 FCN-244F080-G/1 FCN-260A9920 FCN-268D024-G/2F#10X-R10 MP-5T180MUNNA-005 MP-5XRJ45UNNB-003 PCS-E50FA
PCS-XE26LKA PCS-XE26MA+ PCS-XES68MS+ G38A71314B 91-569719-35R 9776-18-6 DX40-50P(55) 1571250010 157-22500-3
MS3471L14-19P L/C 171224-6031 1888020-8 91-569786-35H 91-569786-35M 91-644626-35P 172501-4002 172501-6002 FCN-260C008A/L0 FCN-260C024-AL0 FCN-261Z008 FCN-268D008-G/1K 2000314-1 200331-1 2007498-2 PCR-E28LMDAG1+ PCR-E36FC+ PCSE28FS+ PCS-XE26SLFD+ PCS-XE26SLFDT+ G38A71214B HDRA-E68W1LFDTC-SL+ HDR-E14MSG1+ R88A-CNK81S CRT1ATT02