

REV.	A0	NEW RELEASE	2013.05.24	王亮	X.XX±0.15
DESCRPTION					X.XX±0.05
DATE					ANGLE
NAME					GENERAL TOLERANCE
					2013.01.18
					2013.01.18
					王亮
					簽字
					APPROVED BY
					mm
					1 : 1
					1 of 1
					UNIT
					SCALE
					SHEET
TITLE:		JOINT TECH ELECTRONIC IND. CO., LTD.			
DRAWING NO.:		F1004WV-XPRXXXXXXXXXX			
REV.	A0				

Notes:	1. 已開發Pin數.	
F1004WV-20P	19.00	22.50
F1004WV-19P	18.00	21.50
F1004WV-18P	17.00	20.50
F1004WV-17P	16.00	19.50
F1004WV-16P	15.00	18.50
F1004WV-15P	14.00	17.50
F1004WV-14P	13.00	16.50
F1004WV-13P	12.00	15.50
F1004WV-12P	11.00	14.50
F1004WV-11P	10.00	13.50
F1004WV-10P	9.00	12.50
F1004WV-09P	8.00	11.50
F1004WV-08P	7.00	10.50
F1004WV-07P	6.00	9.50
F1004WV-06P	5.00	8.50
F1004WV-05P	4.00	7.50
F1004WV-04P	3.00	6.50
F1004WV-21P	20.00	23.50
F1004WV-22P	21.00	24.50
F1004WV-23P	22.00	25.50
F1004WV-24P	23.00	26.50
F1004WV-25P	24.00	27.50
F1004WV-26P	25.00	28.50
F1004WV-27P	26.00	29.50
F1004WV-28P	27.00	30.50
F1004WV-29P	28.00	31.50
F1004WV-30P	29.00	32.50
F1004WV-31P	30.00	33.50
F1004WV-32P	31.00	34.50
F1004WV-33P	32.00	35.50
F1004WV-34P	33.00	36.50
F1004WV-35P	34.00	37.50
F1004WV-36P	35.00	38.50

Ordering Information & Dimensions

PART NO.	Dimensions	A	B
F1004WV-20P	22.50	19.00	22.50
F1004WV-19P	21.50	18.00	21.50
F1004WV-18P	20.50	17.00	20.50
F1004WV-17P	19.50	16.00	19.50
F1004WV-16P	18.50	15.00	18.50
F1004WV-15P	17.50	14.00	17.50
F1004WV-14P	16.50	13.00	16.50
F1004WV-13P	15.50	12.00	15.50
F1004WV-12P	14.50	11.00	14.50
F1004WV-11P	13.50	10.00	13.50
F1004WV-10P	12.50	9.00	12.50
F1004WV-09P	11.50	8.00	11.50
F1004WV-08P	10.50	7.00	10.50
F1004WV-07P	9.50	6.00	9.50
F1004WV-06P	8.50	5.00	8.50
F1004WV-05P	7.50	4.00	7.50
F1004WV-04P	6.50	3.00	6.50
F1004WV-21P	23.50	20.00	23.50
F1004WV-22P	24.50	21.00	24.50
F1004WV-23P	25.50	22.00	25.50
F1004WV-24P	26.50	23.00	26.50
F1004WV-25P	27.50	24.00	27.50
F1004WV-26P	28.50	25.00	28.50
F1004WV-27P	29.50	26.00	29.50
F1004WV-28P	30.50	27.00	30.50
F1004WV-29P	31.50	28.00	31.50
F1004WV-30P	32.50	29.00	32.50
F1004WV-31P	33.50	30.00	33.50
F1004WV-32P	34.50	31.00	34.50
F1004WV-33P	35.50	32.00	35.50
F1004WV-34P	36.50	33.00	36.50
F1004WV-35P	37.50	34.00	37.50
F1004WV-36P	38.50	35.00	38.50

RECOMMENDED FCC/FPC DIMENSION
THICKNESS 0.30±0.03mm

SPECIFICATIONS
 Current Rating: 0.5A AC/DC
 Voltage Rating: 50V AC/DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Phosphor Bronze/Tin-plated
 Material: LCP, UL94V-0
 Color: Natural(Black)

① Series No.
 ② Connector type: W=Vertical
 ③ No. of circuits
 ④ R=RoHS
 ⑤ Material: LCP, UL94V-0
 ⑥ Color: B=Black
 ⑦ Plating code for contacts: T1=Tin-plated
 ⑧ Plating code: N=Non-plating
 ⑨ Option code: 00=Standard
 ⑩ Packing code: B=TRAY

SUGGESTED PCB LAYOUT (COMPONENT SIDE)

Notes: 1. 已開發Pin數.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [FFC & FPC Connectors](#) category:

Click to view products by [Joint manufacturer](#):

Other Similar products are found below :

[HFW11R-1STE1H1LF](#) [FH29B-100S-0.2SHW\(99\)](#) [FA5S008HP1](#) [FH29B-120S-0.2SHW\(99\)](#) [FH29B-80S-0.2SHW\(99\)](#) [FHS-16](#) [FPH-2022G](#)
[52610-1075](#) [52610-1275](#) [52610-1934](#) [XF3M\(1\)-1415-1B-R100](#) [501864-3091-TR225](#) [0525594033](#) [086210010340800](#) [086222026001800](#)
[52271-2869-CUT-TAPE](#) [62674-201121DLF](#) [62684-36210E9ALF](#) [52610-1675](#) [52746-1671-TR250](#) [10051922-2810EHLF](#) [6-520415-9](#)
[BD021-09A-A1-0350-0200-0550-LD](#) [SFV6R-1STE9HLF](#) [XF3M-2915-1B-R100](#) [1658549-1](#) [62674-221121ALF](#) [46214008010800](#)
[046298003000883](#) [151660622](#) [842-816-2630-035](#) [AYF530665TA](#) [AYF351525](#) [046296011930846+](#) [AYF352325A](#) [046254020000800+](#)
[FH19C-13S-0.5SH\(99\)](#) [FH39J-51S-0.3SHW\(99\)](#) [AYF355125A](#) [AYF530365TA](#) [FH29B-44S-0.2SHW\(99\)](#) [SFW5R-2STAE9LF](#) [AYF351125A](#)
[AYF350725A](#) [62684-502100AHLF](#) [FH39-61S-0.3SHW\(99\)](#) [AYF414035A](#) [10064555-172520HLF](#) [AYF212335A](#) [504754-2500](#)