



Ordering code

A0800 WR-S-XP XXX
 ① ② ③ ④ ⑤

- ① Series No.
- ② Connector type: WR=Right angle
- ③ Mounting type: S=SMT without boss
- ④ No. of circuits
- ⑤ Option code:
 Blank=Contacts/Matte Tin-plated and Solder tabs/Matte Tin-plated
 D01=Contacts/Gold-flash and Solder tabs/Gold-flash
 D02=Contacts/Gold-plated 3u" and Solder tabs/Gold-flash

SPECIFICATIONS

Current Rating: 0.5A AC,DC
 Voltage Rating: 30V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 200V AC/minute
 Pin Material: Phosphor Bronze/
 Matte Tin-plated or Gold-flash or Gold-plated 3u"
 Solder Tabs: Phosphor Bronze/
 Matte Tin-plated or Gold-flash
 Material: Nylon 6T,UL94V-0
 Color: Natural(Beige)

| Circuit No. | Dimensions | | | |
|-------------|------------|-------|-------|-------|
| | A | B | C | D |
| 02P | 0.80 | 3.80 | 1.90 | 2.38 |
| 03P | 1.60 | 4.60 | 2.70 | 3.18 |
| 04P | 2.40 | 5.40 | 3.50 | 3.98 |
| 05P | 3.20 | 6.20 | 4.30 | 4.78 |
| 06P | 4.00 | 7.00 | 5.10 | 5.58 |
| 07P | 4.80 | 7.80 | 5.90 | 6.38 |
| 08P | 5.60 | 8.60 | 6.70 | 7.18 |
| 10P | 7.20 | 10.20 | 8.30 | 8.78 |
| 12P | 8.80 | 11.80 | 9.90 | 10.38 |
| 14P | 10.40 | 13.40 | 11.50 | 11.98 |
| 15P | 11.20 | 14.20 | 12.30 | 12.78 |
| 16P | 12.00 | 15.00 | 13.10 | 13.58 |
| 17P | 12.80 | 15.80 | 13.90 | 14.38 |
| 20P | 15.20 | 18.20 | 16.30 | 16.78 |

| | | | | | | | |
|------|----------------------|--------------|-------------------|--------------|--------------|------------------------------------|--|
| B2 | ECN NO. EN1001040002 | 2010. 01. 04 | | | | | |
| B1 | REVISE | 2009. 04. 01 | UNIT | SCALE | SHEET | TITLE: | |
| B0 | REVISE | 2009. 03. 19 | mm | | 1 of 2 | 0.80mm PITCH 90° WAFER-SMT TYPE | |
| A5 | REVISE | 2008. 11. 26 | DRAWN BY | | APPROVED BY | | |
| A4 | REVISE | 2008. 04. 08 | 李勤 | | 董正一 | | |
| A3 | REVISE | 2007. 10. 12 | 2006. 02. 07 | | 2006. 02. 07 | | |
| A2 | REVISE | 2007. 07. 26 | GENERAL TOLERANCE | | | | |
| A1 | REVISE | 2006. 04. 15 | X. X±0.25 | ANGLE± | | | |
| A0 | NEW RELEASE | 2006. 02. 07 | X. XX±0.15 | DRAW NO. : | | | |
| REV. | DESCRIPTION | DATE | X. XXX±0.05 | A0800WR-S-XP | | REV. B2 | |



燦達電子工業股份有限公司
 JOINT TECH ELECTRONIC IND. CO., LTD.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Joint Tech](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)