



REV.	DESCRIPTION	DATE	NAME	X.XXX±0.05	ANGLE
B2	EN112050811	2011.12.05	陳錦慶	X.X±0.25	2001.02.01
B1	EN103280080	2011.03.25	陳錦慶	X.XX±0.15	2001.02.01
GENERAL TOLERANCE		2001.02.01			
DRAWN BY		修正一			
APPROVED BY		2001.02.01			
UNIT	SCALE	SHEET	TITLE:		
mm	1 : 1	1 of 1	燦達電子工業股份有限公司		

REV.	DRAW NO.:	A2004WR-2XNP
B2	2.00mm PITCH 90° WAFER	

Circuit	Dimensions	
	A	B
2X02P	2.00	6.00
2X03P	4.00	8.00
2X04P	6.00	10.00
2X05P	8.00	12.00
2X06P	10.00	14.00
2X07P	12.00	16.00
2X08P	14.00	18.00
2X09P	16.00	20.00
2X10P	18.00	22.00
2X11P	20.00	24.00
2X12P	2.00	6.00
2X13P	4.00	8.00
2X14P	6.00	10.00
2X15P	8.00	12.00
2X16P	10.00	14.00
2X17P	12.00	16.00
2X18P	14.00	18.00
2X19P	16.00	20.00
2X20P	18.00	22.00

SPECIFICATIONS  
 Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage: 800V AC/minute  
 Pin Material: Brass

P/N LEGEND  
 A2004 WR-2XNP XXX  
 ① Series No.  
 ② Connector type: WR=Right angle  
 ③ No. of circuits  
 ④ Option code:  
 Blank=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:3.00mm  
 WH=Nylon 66-V0, Natural(White), Tin-plated, Dim. F:3.00mm  
 BL=Nylon 66-V0, Blue(660C), Tin-plated, Dim. F:3.00mm  
 GR=Nylon 66-V0, Green(347C), Tin-plated, Dim. F:3.00mm  
 46=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:3.00mm  
 46G=Nylon 46-V0, Natural(Beige), Gold-flash, Dim. F:3.00mm  
 Y01=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:2.50mm  
 Y11=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:2.50mm  
 Y21=Nylon 46-V0, Natural(Beige), Gold-flash, Dim. F:2.50mm  
 Y02=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:2.00mm  
 Y12=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:2.00mm

D

C

B

A

D

C

B

A

4

3

2

1

4

3

2

1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Joint Tech](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)