



| | | | | | |
|-------------------|--------------|------------|--------------|------------|------------|
| REV. | DESCRIPTION | DATE | NAME | X.XXX±0.05 | ANGLE |
| B2 | EN112050811 | 2011.12.05 | 陳錦慶 | X.X±0.25 | 2001.02.01 |
| B1 | EN1103280080 | 2011.03.25 | 陳錦慶 | X.XX±0.15 | 2001.02.01 |
| GENERAL TOLERANCE | | 2001.02.01 | | | |
| DRAWN BY | | 修正一 | | | |
| APPROVED BY | | 2001.02.01 | | | |
| UNIT | SCALE | SHEET | TITLE: | | |
| mm | 1:1 | 1 of 1 | 燦達電子工業股份有限公司 | | |

| | | | | | |
|------------|--------------|---------------------------|------|------------|-------|
| REV. | DESCRIPTION | DATE | NAME | X.XXX±0.05 | ANGLE |
| B2 | A2004WR-2XNP | | | | |
| DRAWN NO.: | | A2004WR-2XNP | | | |
| TITLE: | | 2.00mm PITCH 90° WAFER | | | |

| Circuit | Dimensions | |
|---------|------------|-------|
| | A | B |
| 2X02P | 2.00 | 6.00 |
| 2X03P | 4.00 | 8.00 |
| 2X04P | 6.00 | 10.00 |
| 2X05P | 8.00 | 12.00 |
| 2X06P | 10.00 | 14.00 |
| 2X07P | 12.00 | 16.00 |
| 2X08P | 14.00 | 18.00 |
| 2X09P | 16.00 | 20.00 |
| 2X10P | 18.00 | 22.00 |
| 2X11P | 20.00 | 24.00 |

| Circuit | Dimensions | |
|---------|------------|-------|
| | C | D |
| 2X02P | 4.70 | --- |
| 2X12P | 22.00 | 26.00 |
| 2X13P | 24.00 | 28.00 |
| 2X14P | 26.00 | 30.00 |
| 2X15P | 28.00 | 32.00 |
| 2X16P | 30.00 | 34.00 |
| 2X17P | 32.00 | 36.00 |
| 2X18P | 34.00 | 38.00 |
| 2X19P | 36.00 | 40.00 |
| 2X20P | 38.00 | 42.00 |
| 2X21P | 40.00 | 44.00 |
| 2X22P | 42.00 | 46.00 |
| 2X23P | 44.00 | 48.00 |
| 2X24P | 46.00 | 50.00 |

SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass

① Series No. A2004 WR-2XNP XXX ④
 ② Connector type: WR=Right angle
 ③ No. of circuits
 ④ Option code:
 Blank=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:3.00mm
 WH=Nylon 66-V0, Natural(White), Tin-plated, Dim. F:3.00mm
 BL=Nylon 66-V0, Blue(660C), Tin-plated, Dim. F:3.00mm
 GR=Nylon 66-V0, Green(347C), Tin-plated, Dim. F:3.00mm
 46=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:3.00mm
 46G=Nylon 46-V0, Natural(Beige), Gold-flash, Dim. F:3.00mm
 Y01=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:2.50mm
 Y11=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:2.50mm
 Y21=Nylon 46-V0, Natural(Beige), Gold-flash, Dim. F:2.50mm
 Y02=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:2.00mm
 Y12=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:2.00mm

P/N LEGEND

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Joint Tech](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)