



SPECIFICATIONS
 Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass

Blank=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:3.00mm
 WH=Nylon 66-V0, Natural(White), Tin-plated, Dim. F:3.00mm
 BL=Nylon 66-V0, Blue(660C), Tin-plated, Dim. F:3.00mm
 GR=Nylon 66-V0, Green(347C), Tin-plated, Dim. F:3.00mm
 46=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:3.00mm
 46G=Nylon 46-V0, Natural(Beige), Gold-flash, Dim. F:3.00mm
 Y01=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:2.50mm
 Y11=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:2.50mm
 Y21=Nylon 46-V0, Natural(Beige), Gold-flash, Dim. F:2.50mm
 Y02=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:2.00mm
 Y12=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:2.00mm

- ① Series No. A2004 WR-2XNP XXX
- ② Connector type: WR=Right angle
- ③ No. of circuits
- ④ Option code:

Circuit	Dimensions			
	No. A	No. B	No. C	No. D
2X02P	2.00	6.00	4.70	---
2X03P	4.00	8.00	6.70	2.00
2X04P	6.00	10.00	8.70	4.00
2X05P	8.00	12.00	10.70	6.00
2X06P	10.00	14.00	12.70	8.00
2X07P	12.00	16.00	14.70	10.00
2X08P	14.00	18.00	16.70	12.00
2X09P	16.00	20.00	18.70	14.00
2X10P	18.00	22.00	20.70	16.00
2X11P	20.00	24.00	22.70	18.00

REV.	DESCRIPTION	DATE	NAME	X.XXX±0.05	ANGLE
B2	EN112050511	2011.12.05	陈锦展	X.X±0.25	2001.02.01
B1	EN103280080	2011.03.25	陈锦展	X.XX±0.15	2001.02.01
GENERAL TOLERANCE					
DRAWN BY 姜正一					
APPROVED BY					
UNIT mm					
SCALE 1 : 1					
SHEET 1 of 1					
TITILE: 燦達電子工業股份有限公司					
JOINT TECH ELECTRONIC IND. CO., LTD.					
DRAW NO.: A2004WR-2XNP					
REV.	2.00mm PITCH 90° WAFER				
B2					

P/N LEGEND

A2004 WR-2XNP XXX
 ① ② ③ ④

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Joint Tech](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)