



REV.	DESCRIPTION	DATE	NAME	DATE	REV.
B2	EN112050811	2011.12.05	陳錦慶	X.XX±0.25	ANGLE
B1	EN103280080	2011.03.25	陳錦慶	X.XX±0.15	GENERAL TOLERANCE

UNIT	SCALE	SHEET
mm	1 : 1	1 of 1
APPROVED BY	DRAWN BY	DATE
修正一	2001.02.01	2001.02.01
GENERAL TOLERANCE		
X.XX±0.25		
X.XX±0.15		

Circuit	No.	Dimensions
2X02P	2.00	6.00 4.70
2X03P	4.00	8.00 6.70
2X04P	6.00	10.00 8.70
2X05P	8.00	12.00 10.70
2X06P	10.00	14.00 12.70
2X07P	12.00	16.00 14.70
2X08P	14.00	18.00 16.70
2X09P	16.00	20.00 18.70
2X10P	18.00	22.00 20.70
2X11P	20.00	24.00 22.70

Circuit	No.	Dimensions
2X12P	22.00	26.00 24.70
2X13P	24.00	28.00 26.70
2X14P	26.00	30.00 28.70
2X15P	28.00	32.00 30.70
2X16P	30.00	34.00 32.70
2X17P	32.00	36.00 34.70
2X18P	34.00	38.00 36.70
2X19P	36.00	40.00 38.70
2X20P	38.00	42.00 40.70
2X21P	40.00	44.00 42.70
2X22P	42.00	46.00 44.70

Dimensions	No.	Circuit
20.00	A	2X02P
18.00	B	2X03P
16.00	C	2X04P
14.00	D	2X05P
12.00	A	2X06P
10.00	B	2X07P
8.00	C	2X08P
6.00	D	2X09P
4.00	A	2X10P
2.00	B	2X11P
2.00	C	2X12P
2.00	D	2X13P
2.00	A	2X14P
2.00	B	2X15P
2.00	C	2X16P
2.00	D	2X17P
2.00	A	2X18P
2.00	B	2X19P
2.00	C	2X20P
2.00	D	2X21P
2.00	A	2X22P

Pin Material: Brass
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1000MΩ Min.
 Contact Resistance: 10mΩ Max.
 Temperature Range: -25°C ~ +85°C
 Voltage Rating: 250V AC,DC
 Current Rating: 3A AC,DC

SPECIFICATIONS
 Y12=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:2.00mm
 Y02=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:2.00mm
 Y21=Nylon 46-V0, Natural(Beige), Gold-flash, Dim. F:2.50mm
 Y11=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:2.50mm
 Y01=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:2.50mm
 46G=Nylon 46-V0, Natural(Beige), Gold-flash, Dim. F:3.00mm
 46=Nylon 46-V0, Natural(Beige), Tin-plated, Dim. F:3.00mm
 GR=Nylon 66-V0, Green(347C), Tin-plated, Dim. F:3.00mm
 BL=Nylon 66-V0, Blue(660C), Tin-plated, Dim. F:3.00mm
 WH=Nylon 66-V0, Natural(White), Tin-plated, Dim. F:3.00mm
 Blank=Nylon 66-V0, Gray(7528C), Tin-plated, Dim. F:3.00mm

① Series No. A2004 WR-2XNP XXX
 ② Connector type: WR=Right angle
 ③ No. of circuits
 ④ Option code:

P/N LEGEND
 A B C D
 Dimensions

TITLE:
 燦達電子工業股份有限公司
 JOINT TECH ELECTRONIC IND. CO., LTD.

UNIT SCALE SHEET
 mm 1 : 1 1 of 1
 DRAWN BY APPROVED BY
 2001.02.01 2001.02.01
 GENERAL TOLERANCE
 X.XX±0.25
 X.XX±0.15
 ANGLE
 X.XX±0.05

REV. DESCRIPTION DATE NAME DATE REV.
 B2 EN112050811 2011.12.05 陳錦慶 X.XX±0.25
 B1 EN103280080 2011.03.25 陳錦慶 X.XX±0.15

DRAW NO.: A2004WR-2XNP
 REV. B2

2.00mm PITCH
 90° WAFER

4 3 2 1

A B C D

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Joint Tech](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)