



|      |             |            |           |                   |          |            |              |    |
|------|-------------|------------|-----------|-------------------|----------|------------|--------------|----|
| REV. | DESCRIPTION | DATE       | X.XX±0.05 | ANGLE             | DRAWN BY | 2010.01.13 | EN1001130026 | B5 |
| B0   | NEW RELEASE | 2005.10.07 | X.XX±0.15 | GENERAL TOLERANCE | 陳耀元      | 2007.05.18 |              | B4 |
| B1   | REVISION    | 2005.11.24 | X.X±0.25  | GENERAL TOLERANCE | 修正一      | 2006.05.11 |              | B3 |
| B2   | REVISION    | 2006.05.07 |           | GENERAL TOLERANCE | 陳耀元      | 2006.05.11 |              | B2 |
| B3   | REVISION    | 2006.05.11 |           | GENERAL TOLERANCE | 修正一      | 2005.03.03 |              | B1 |
| B4   | REVISION    | 2007.05.18 |           | GENERAL TOLERANCE | 陳耀元      | 2007.05.18 |              | B0 |
| B5   | REVISION    | 2010.01.13 |           | GENERAL TOLERANCE | 陳耀元      | 2010.01.13 |              |    |

| Dimensions |       | Circuit |       |
|------------|-------|---------|-------|
| No.        | A     | B       | C     |
| 02P        | 2.00  | 6.00    | 1.50  |
| 03P        | 4.00  | 8.00    | 1.46  |
| 04P        | 6.00  | 10.00   | 3.46  |
| 05P        | 8.00  | 12.00   | 5.46  |
| 06P        | 10.00 | 14.00   | 7.46  |
| 07P        | 12.00 | 16.00   | 9.46  |
| 08P        | 14.00 | 18.00   | 11.46 |
| 09P        | 16.00 | 20.00   | 13.46 |
| 10P        | 18.00 | 22.00   | 15.46 |
| 11P        | 20.00 | 24.00   | 17.46 |
| 12P        | 22.00 | 26.00   | 19.46 |
| 13P        | 24.00 | 28.00   | 21.46 |
| 14P        | 26.00 | 30.00   | 23.46 |
| 15P        | 28.00 | 32.00   | 25.46 |
| 16P        | 30.00 | 34.00   | 27.46 |
|            | 32.90 |         |       |

**SPECIFICATIONS**  
 Series No. A2006 WV-XP XXX  
 Ordering code  
 ① Series No.  
 ② Connector type: WV=Vertical  
 ③ No. of circuits  
 ④ Option code:  
 Blank=Color/Beige; Dim. E=3.20mm  
 BK =Color/Black; Dim. E=3.20mm  
 Y01 =Color/Beige; Dim. E=2.10mm  
 Pin Material: Brass/Gold-flash  
 Material: Nylon 46,UL94V-0  
 Color: Beige or Black  
 Withstanding Voltage: 1000V AC/minute  
 Insulation Resistance: 1000MΩ Min.  
 Contact Resistance: 30mΩ Max.  
 Temperature Range: -25°C ~ +85°C  
 Voltage Rating: 250V AC,DC  
 Current Rating: 3A AC,DC

燦達電子工業股份有限公司  
 JOINT TECH ELECTRONIC IND. CO., LTD.  
 TITLE: 2.00mm PITCH 180° WAFER  
 APPROVED BY: 陳耀元  
 DRAWN BY: 陳耀元  
 SCALE: 1 of 1  
 SHEET: 4

DRAW NO.: A2006WV-XP  
 REV. B5

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Joint Tech](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)