



TYPE 1

**SPECIFICATIONS**

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 800V AC/minute  
 Pin Material: Brass/Tin-plated  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
A2502WR-02P1	2.50	7.50
A2502WR-03P1	5.00	10.00
A2502WR-04P1	7.50	12.50
A2502WR-05P1	10.00	15.00
A2502WR-06P1	12.50	17.50
A2502WR-07P1	15.00	20.00
A2502WR-08P1	17.50	22.50
A2502WR-09P1	20.00	25.00
A2502WR-10P1	22.50	27.50
A2502WR-11P1	25.00	30.00
A2502WR-12P1	27.50	32.50
A2502WR-13P1	30.00	35.00
A2502WR-14P1	32.50	37.50
A2502WR-15P1	35.00	40.00

UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	
DRAWN BY	APPROVED BY	<b>2.50mm PITCH</b> <b>90° WAFER, TYPE 1</b>	
李勤	董正一		
2006.05.14	2006.05.14		
GENERAL TOLERANCE			
A0	NEW RELEASE	2006.05.14	DRAW NO. : A2502WR-XP1
REV.	DESCRIPTION	DATE	
		X. X±0.25	ANGLE±
		X. XX±0.15	
		X. XXX±0.05	
			REV. A0

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Joint Tech](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)