



### SPECIFICATIONS

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 500MΩ Min  
 Withstanding Voltage: 800V AC/minute  
 Pin Material: Brass/Tin-plated  
 Material: Nylon 66,UL94V-0  
 Color: Natural(White)

### Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2540WR-02P1	2.50	5.00
A2540WR-03P1	5.00	7.50
A2540WR-04P1	7.50	10.00
A2540WR-05P1	10.00	12.50
A2540WR-06P1	12.50	15.00
A2540WR-07P1	15.00	17.50
A2540WR-08P1	17.50	20.00
A2540WR-09P1	20.00	22.50
A2540WR-10P1	22.50	25.00
A2540WR-11P1	25.00	27.50
A2540WR-12P1	27.50	30.00
A2540WR-13P1	30.00	32.50
A2540WR-14P1	32.50	35.00
A2540WR-15P1	35.00	37.50

UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	2.50mm PITCH 90° WAFER
DRAWN BY 李勤 2005.12.23		APPROVED BY 董正一 2005.12.23	
A2	REVISE	2006.09.18	GENERAL TOLERANCE
A1	REVISE	2006.05.15	X. X±0.25
A0	NEW RELEASE	2005.12.23	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05
			DRAW NO. : A2540WR-XP1
			REV. A2

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Joint Tech](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)