



03P~12P

02P

SPECIFICATIONS

Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-2
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C3030HF-02P	3.00	6.80
C3030HF-03P	6.00	9.80
C3030HF-04P	9.00	12.80
C3030HF-05P	12.00	15.80
C3030HF-06P	15.00	18.80
C3030HF-07P	18.00	21.80
C3030HF-08P	21.00	24.80
C3030HF-09P	24.00	27.80
C3030HF-10P	27.00	30.80
C3030HF-11P	30.00	33.80
C3030HF-12P	33.00	36.80

				UNIT	SCALE	SHEET	TITLE:
				mm		1 of 1	
				DRAWN BY	APPROVED BY		3.00mm PITCH HOUSING-RECEPTACLE, SINGLE ROW, MICRO-FIT
				董正一	董正一		
				2002.08.13	2002.08.13		
B2	REVISE	2008.07.16	GENERAL TOLERANCE				
B1	REVISE	2008.07.01	X.X±0.25	ANGLE±			
B0	NEW RELEASE	2005.12.14	X.XX±0.15				
REV.	DESCRIPTION	DATE	X.XXX±0.05			DRAW NO. :	REV.
						C3030HF-XP	B2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Joint Tech](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)