



2X01P

**SPECIFICATIONS**

Current Rating: 5A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Material: Nylon 66,UL94V-2  
 Color: Black

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
C3030HM-2X01P	---	3.85
C3030HM-2X02P	3.00	6.85
C3030HM-2X03P	6.00	9.85
C3030HM-2X04P	9.00	12.85
C3030HM-2X05P	12.00	15.85
C3030HM-2X06P	15.00	18.85
C3030HM-2X07P	18.00	21.85
C3030HM-2X08P	21.00	24.85
C3030HM-2X09P	24.00	27.85
C3030HM-2X10P	27.00	30.85
C3030HM-2X11P	30.00	33.85
C3030HM-2X12P	33.00	36.85

		UNIT	SCALE	SHEET		TITLE:	
		mm		1 of 1		3.00mm PITCH HOUSING-PLUG, MICRO-FIT	
		DRAWN BY		APPROVED BY		DRAW NO. :	
		董正一		董正一		C3030HM-2XNP	
		2001.02.01		2001.02.01		REV. B1	
		GENERAL TOLERANCE					
B1	REVISE	2007.04.16	X. X±0.25	ANGLE±			
B0	NEW RELEASE	2005.12.14	X. XX±0.15				
REV.	DESCRIPTION	DATE	X. XXX±0.05				

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Joint Tech](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)