



REV.	DESCRIPTION	DATE	NAME	X.XX±0.05
A2	ERI409020005	2014.09.02	黃煥有	X.XX±0.25
A1	EN1407230001	2014.07.22	劉包根	X.XX±0.15
A0	NEW RELEASE	2013.12.09	王亮	X.XX±0.05

  

UNIT	SCALE	SHEET
mm	1 : 1	1 of 3

  

DRAWN BY	APPROVED BY	2013.09.17	GENERAL TOLERANCE
王亮	翁志昇	2013.09.17	

  

REV.	DESCRIPTION	DATE	NAME
A2	ERI409020005	2014.09.02	黃煥有
A1	EN1407230001	2014.07.22	劉包根
A0	NEW RELEASE	2013.12.09	王亮

PART NO.	Dimensions	Dimensions	PART NO.
2X01P	---	6.65	2X07P
2X02P	3.00	9.65	2X08P
2X03P	6.00	12.65	2X09P
2X04P	9.00	15.65	2X10P
2X05P	12.00	18.65	2X11P
2X06P	15.00	21.65	2X12P

  

Dimensions	Dimensions	PART NO.
A	B	A
39.65	33.00	B

Ordering Information & Dimensions

**SPECIFICATIONS**  
 Current Rating: 5A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Pin Material: Brass/Tin-plated&Matter Tin-plated  
 Material: LCP,UL94V-0  
 Color: Black

Ordering code  
 C3030 WY-F-2XNP N L B T1 N XX L  
 ① Series No.  
 ② Connector type: W=Vertical  
 ③ Mounting type: F=With foot  
 ④ No. of circuits  
 ⑤ N=Halogen Free  
 ⑥ Material: L=LCP  
 ⑦ Color: B=Black  
 ⑧ Plating code for contacts: T1=Tin-plated/Matter Tin-plated  
 ⑨ Plating code for solder tabs: N=Non-plating  
 ⑩ Option code: 00=Standard 01=Matter Tin-plated  
 ⑪ Packing code: L=Tape & Reel(With cap or Mylar)

3.00mm PITCH 180° WAFER,  
 MICRO-FIT

聯達電子工業股份有限公司  
 JOINT TECH ELECTRONIC IND. CO., LTD.

UNIT	SCALE	SHEET
mm	1 : 1	1 of 3

  

DRAWN BY	APPROVED BY	2013.09.17	GENERAL TOLERANCE
王亮	翁志昇	2013.09.17	

  

REV.	DESCRIPTION	DATE	NAME
A2	ERI409020005	2014.09.02	黃煥有
A1	EN1407230001	2014.07.22	劉包根
A0	NEW RELEASE	2013.12.09	王亮

TITLE:  
 DRAW NO.: C3030WY-F-2XNPXXXXXXXXXX  
 REV. A2

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Joint Tech](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)