


SEC:A-A



SEC:B-B

Ordering Information & Specifications

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
C4255M-TBE-A	AWG#18-#24	3.10mm(max)	Brass	Tin-plated	5,000pcs
C4255M-HBE-A	AWG#18-#24	3.10mm(max)	Brass	Gold-flash 1u"	5,000pcs
C4255M-HBE-A1	AWG#18-#24	3.10mm(max)	Brass	Gold-plated 15u"	5,000pcs
C4255M-GPE-A	AWG#18-#24	3.10mm(max)	Phosphor Brass	All Gold-flash 1u"	5,000pcs

Note:E-Stamping before Tin-plated or Gold-plated

				燦達電子工業股份有限公司 JOINT TECH ELECTRONIC IND. CO., LTD.			
		UNIT		SCALE		SHEET	
		mm		1 : 1		1 of 1	
		DRAWN BY		APPROVED BY		TITLE: 4.20mm PITCH CRIMP TERMINAL-MALE, MINI-FIT	
		朱恆秀		謝瑞清			
		2009.04.02		2009.04.02			
		GENERAL TOLERANCE					
		X. X±0.25		ANGLE±		DRAW NO. : C4255M-XX-A	
		X. XX±0.15					
		X. XXX±0.05					
REV.	DESCRIPTION	DATE	NAME			REV.	A3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Joint Tech](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)