



SPECIFICATIONS
 Current Rating: 10A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin-plated
 Metal Band: Brass/Tin-plated
 Material: Nylon 6T,UL94V-0
 Color: Natural(Black)

REV.	DESCRIPTION	DATE	NAME	X.XX±0.05	ANGLE
A1	EN1107280313	2011.07.28	肖勇	X.X±0.25	GENERAL TOLERANCE
A0	NEW RELEASE	2007.04.25	修正一	X.XX±0.15	2007.04.25
				歐洲小強	修正一
				2007.04.25	APPROVED BY
				1 of 1	SHEET
				mm	SCALE
					UNIT

TITLE: 燦達電子工業股份有限公司
 P/N:C5080WR-04P
 5.08mm PITCH
 90° WAFER

DRW NO.: C5080WR-04P
 REV. A1

Ordering code
 C5080 WR-04P XXX
 ① Series No.
 ② Connector type: WR=Right angle
 ③ No. of circuits
 ④ Option code:
 Blank=Nylon6T,V-0; Color: Natural(Black)

D

C

B

A

4

3

2

1

4

3

2

1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Joint Tech](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)