


**EX-5**

**EX-6**

This PLCC Extraction Tool extracts a range of PLCC sizes from 20 pins through 1 28 pins from any socket without damage to the chip. Spring loaded one-hand design requires no pulling, just squeeze the handles and chip is lifted from the socket. Machined stainless steel for long life.

SPECIFICATIONS	EX-5	EX-6
<b>FUNCTION</b>	Extract	Extract
<b>CHIP PACKAGE TYPE</b>	PLCC	PLCC
<b>PIN COUNT</b>	20-128	20-128
<b>FEATURES</b>	ESD Safe Handles. Spring Loaded One-Handed Operation.	ESD Safe Handles. Spring Loaded One-Handed Operation.
<b>MATERIAL</b>	Stainless Steel	Stainless Steel, ABS Handles
<b>LENGTH</b>	4" (100mm)	4" (100mm)
<b>WEIGHT</b>	0.084 lbs (38.10g)	0.09 lbs (40.82g)
<b>UPC NO.</b>	811490010734	811490010741

**MADE FOR LIFE®**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pliers & Tweezers](#) category:*

*Click to view products by [Jonard Industries](#) manufacturer:*

Other Similar products are found below :

[0031](#) [32750](#) [PN-5050/38D](#) [PG-TP-30D](#) [PG-DP-18-N](#) [4-1532129-2](#) [77 12 115](#) [0037](#) [T0058765801](#) [RT400SGSET2](#) [571](#) [76C](#) [MICROFOX-SP-1\\_DB](#) [37 31 125](#) [RX 8130](#) [37 33 125](#) [DRP10N](#) [36 12 130](#) [0036](#) [64 11 115](#) [T3627B 7](#) [6211-06](#) [6214-45](#) [6217-05](#) [6231-07](#) [6231-08](#) [6411-06](#) [DP20N](#) [PN 5050/10D](#) [TR 25 15](#) [TR 25 P A](#) [TR 30 58 R A](#) [TR 30 V](#) [TR 5000](#) [TR 5000 10 D](#) [TR 5000 PG](#) [MICROFOX-SP\\_DB](#) [CUTFOX-SE LM](#) [CUTFOX-SE LM\\_DB](#) [TR 58 R A](#) [27388](#) [43333](#) [102ACAX](#) [103ACA](#) [141SAP](#) [150SAD](#) [150SAMB](#) [150SAMF](#) [151SA](#) [20AS](#)