


JIC-955

JIC-950C

Designed to cut and insert 22 and 24-gauge wire into terminal blocks, this multipurpose wire insertion tool is the perfect tool for performing several critical functions for wire insertion. This insertion tool features the following:

- Wire cutter cuts 22 and 24 AWG (0.65 mm and 0.51 mm diameter) wire
- Hook on back of unit is used for jumper and back-tap removal
- Bit inserts 22 and 24 AWG (0.65 mm and 0.51 mm diameter diameter) wire into the appropriate terminal block
- Ideal for use on 3-beam (112-type) and 4-beam (78-type) terminal blocks in Cosmic & Cosmic II distributing frames

This replacement blade for JIC-950C is used for inserting 22 and 24 AWG wire into an appropriate terminal block.

SPECIFICATIONS	JIC-955	JIC-950C
BLOCK TYPE	3-beam (112-type) and 4-beam (78-type) terminal blocks	3-beam (112-type) and 4-beam (78-type) terminal blocks
FUNCTIONS		Insertion, Cutting
CABLE DIAMETER		22 and 24 AWG (0.65 mm and 0.51 mm diameter)
WEIGHT	0.029 lbs (13.15g)	0.280 lbs (127.01g)
UPC NO.	811490014206	811490011991

MADE FOR LIFE®

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wire Stripping & Cutting Tools](#) category:

Click to view products by [Jonard Industries](#) manufacturer:

Other Similar products are found below :

[6-690504-4](#) [693855-1](#) [813066-2](#) [844764-5](#) [844765-5](#) [1-240642-7](#) [133900-001](#) [1-356885-4](#) [1424635-1](#) [1424649-1](#) [1424650-1](#) [1440-0013-84](#)
[1-458031-5](#) [1-458030-5](#) [MT10-250Q](#) [1755](#) [2-539783-7](#) [L-5211](#) [1633578-3](#) [F10-10Q](#) [1-844765-9](#) [251465-1](#) [R282066100](#) [313808-1](#)
[CST596711](#) [458031-9](#) [462839-1](#) [467281-1](#) [4-690504-2](#) [406339-3](#) [L-4994](#) [45-265](#) [453653-1](#) [45-418](#) [455177-1](#) [455671-4](#) [458144-8](#) [462548-](#)
[1](#) [464661-1](#) [224186-1](#) [679746-1](#) [809687-1](#) [852080-2](#) [856695-8](#) [11-40-4082](#) [458030-1](#) [679326-7](#) [605744-1](#) [690784-2](#) [844764-1](#)