



**PROTECTION PRODUCTS DESCRIPTION**

The SM712 transient voltage suppressor (TVS) diode is designed for asymmetrical (12V to -7V) protection in multi-point data transmission standard RS-485 applications. The SM712 may be used to protect devices from transient voltages resulting from electrostatic discharge (ESD). Electrical fast transients (EFT). And lightning.

The SM712 features 400 Watts ( $t_p=8/20\mu s$ ) of power handling capability to accommodate the higher transient voltage levels which may be expected in extended common mode applications. This provides higher equipment reliability and eliminates the “guess work” required when using zener diodes that are not rated to handle such transient conditions.

The SM712 replaces four discrete components by integrating two 12V and two 7V TVS diodes in a single package. The integrated design aids in reducing voltage over-shoot associated with trace inductance. The low clamping voltage of the SM712 minimizes the stress on the protected transceiver. The SOT23 package allows flexibility in the design of “crowded” circuit boards.




**Applications Features**

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>● Protection of RS-485 transceivers with extended common-mode range</li> <li>● Security systems</li> <li>● Automatic Teller Machines</li> <li>● HFC systems</li> <li>● Networks</li> </ul> | <ul style="list-style-type: none"> <li>● 400Watts Peak Pulse Power per (<math>t_p=8/20\mu s</math>)</li> <li>● Transient protection for asymmetrical data lines to IEC61000-4-2(ESD) 15kV(air), 8kV(contact) IEC61000-4-4(EFT) 40A(5/50 <math>\mu s</math>) IEC61000-4-5(Lightning):12A(8/20<math>\mu s</math>)</li> <li>● Protects two +12V to -7V lines</li> <li>● Low capacitance; Low clamping voltage</li> <li>● Solid-state silicon avalanche technology</li> </ul> |
|---|---|

**Ordering Information Mechanical Data**

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>● Device: SM712</li> <li>● Package: SOT-23</li> <li>● Packing: Tape &amp; Reel</li> <li>● Quantity per reel: 3,000pcs</li> </ul> | <ul style="list-style-type: none"> <li>● JEDEC SOT-23 Package</li> <li>● Molding compound flammability Rating: UL 94V-0</li> <li>● High temperature soldering guaranteed: 260°C/10s</li> <li>● Material: Halogen free</li> </ul> |
|---|--|

**Marking code Diagram Schematic**



**ABSOLUTE MACIMUM RATING**

Parameters	Symbol	Value	Unit
Peak Pulse Power (8/20 $\mu s$ )	PPP	400	W
Peak Pulse Current ( $t_p=8/20\mu s$ )	I <sub>PP</sub>	17	A
Operating temperature	T <sub>OPT</sub>	-55-+125	°C
Storage temperature range	T <sub>STG</sub>	-55-+150	°C


**Electrical Characteristics (Ratings at 25°C ambient temperature unless otherwise specified).**

Symbol	Parameter	Test Condition	Pin 1 to 3 and Pin 2 to 3 (12V) TVS			Pin 3 to 1 and Pin 3 to 2 (7V) TVS			Units
			Min	Typ	Max	Min	Typ	Max	
V <sub>RWM</sub>	Reverse Working Voltage	Pin 3 to 1 or Pin 2 to 1			12			7	V
V <sub>BR</sub>	Reverse Breakdown Voltage	I <sub>T</sub> = 1mA	13.3			7.5			V
I <sub>R</sub>	Reverse Leakage Current	V <sub>R</sub> = V <sub>RWM</sub>			1			20	μA
V <sub>C1</sub>	Clamping Voltage 1	I <sub>PP</sub> = 5A, t <sub>p</sub> = 8/20μs			20			10	V
V <sub>C2</sub>	Clamping Voltage 2	I <sub>PP</sub> = 17A, t <sub>p</sub> = 8/20μs			26			12	V
C <sub>J1</sub>	Junction Capacitance 1	V <sub>R</sub> = 0V, f = 1MHz			75			75	pF
C <sub>J2</sub>	Junction Capacitance 2	V <sub>R</sub> = V <sub>RWM</sub> , f = 1MHz		45			45		pF




**ELECTRICAL CHARACTERISTICS CURVE**


**Non-Repetitive Peak Pulse Power vs. Pulse Time**




**Pulse Waveform**




**Capacitance vs. Reverse Voltage**




**Power Derating Curve**



**Clamping Voltage vs. Peak Pulse Current**



**SOT-23 PACKAGE OUTLINE** Plastic surface mounted package




SYMBOL	DIMENSIONS	
	MIN.	MAX.
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°

Unit: mm

**Precautions: PCB Design**

(Recommended land dimensions for SOT-23 diode. Electrode patterns for PCBs)



Note:  
 1. Controlling dimension: in millimeters.  
 2. General tolerance: ±0.05mm.  
 3. The pad layout is for reference purposes only.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [ESD Suppressors / TVS Diodes](#) category:*

*Click to view products by [Juxing Electronic Technology](#) manufacturer:*

Other Similar products are found below :

[60KS200C](#) [D18V0L1B2LP-7B](#) [D5V0F4U5P5-7](#) [NTE4902](#) [P4KE27CA](#) [P6KE11CA](#) [P6KE8.2A](#) [SA60CA](#) [SA64CA](#) [SMBJ12CATR](#)  
[SMBJ33CATR](#) [SMBJ6.5A](#) [SMBJ8.0A](#) [ESD101-B1-02ELS E6327](#) [ESD112-B1-02EL E6327](#) [ESD7451N2T5G](#) [19180-510](#) [CPDT-5V0USP-](#)  
[HF](#) [3.0SMCJ33CA-F](#) [3.0SMCJ36A-F](#) [HSPC16701B02TP](#) [JANTX1N6126A](#) [D3V3Q1B2DLP3-7](#) [D55V0M1B2WS-7](#) [SCM1293A-04SO](#)  
[ESD200-B1-CSP0201 E6327](#) [SM12-7](#) [CEN955 W/DATA](#) [VESD12A1A-HD1-GS08](#) [CPDQC5V0-HF](#) [D1213A-01LP4-7B](#) [ESD101-B1-02EL](#)  
[E6327](#) [AOZ8808DI-03](#) [5KP15A](#) [5KP48A](#) [5KP90A](#) [ESD3V3D7-TP](#) [15KPA36A-LF](#) [P4KE56CA](#) [P4KE68A](#) [P4KE91CATR](#) [P6KE120A](#)  
[P6KE13CA](#) [P6KE43CA](#) [P6KE6.8CA](#) [P6KE8.2](#) [P6SMBJ20CA](#) [JANTX1N6072A](#) [SR2835ESKG](#) [SA90CA](#)