
Model	Name	Use With:	Model	Name	Use With:	
213-CON	Analog Output Connector	Instruments with 12-pin analog	7001-PNL	Metal Plate	7001	
237-BAN-3A	Triax to Banana Plug	connectors 4200-SCS, 7072, 7072-HV, DMMs	7011-KIT-R	Female 96-pin Connector Kit	7011-C, 7012-C, 7013-C, 7015-C, 7018-C	
237-BNC-TRX	3-Lug Female Triax to Male BNC Connector with guard disconnected	237, 4200-SCS, 6517A, 6517B, 7078-TRX cables	7011-MTR	Bulkhead Mount 96-pin Male Connector	7011-KIT-R, 7011-C, 7012-C, 7013-C, 7015-C, 7018-C	
237-TRX-BAR	3-Lug Triax Female to Female Barrel Adapter	2635, 2635A, 2636, 2636A, 4200-SCS, Triax interconnect	7011-ST	Extra Screw Terminal Board	7011-5	
	Triax Male-Female Adapter with		7012-ST	Extra Screw Terminal Board	7012-8	
237-TRX-NG	guard disconnected	237, 6517A, 6517B, 7072, 7072-HV	7013-ST	Extra Screw Terminal Board	7013-5	
237-TRX-T	3-slot Male to Dual 3-Lug Female Triax Tee Adapter	4200-SCS, 7072, 7072-HV, 7078-TRX cables	7014-ST	Extra Screw Terminal Board	7014	
	3-Lug Female Triax Bulkhead		7015-ST	Extra Screw Terminal Board	7015-S	
237-TRX-TBC	Connector	7072, 7072-HV, 7078-TRX cables	7018-ST	Extra Screw Terminal Board	7018-5	
2182-325A	Silver Solder for use with 2182-KIT	2182A	7072-TRT	Triax Removal Tool	707B, 708B	
2182-KIT	Low-Thermal Connector with Strain	2182A, SC-93	7074-CIT	Contact Extraction Tool	7152-KIT, 7152-MTR	
	Relief (LEMO)	,	7074-HCT	Hand Crimping Tool	7152-KIT, 7152-MTR	
2188	Low-Thermal Calibration Shorting Plug	2182A	7078-CIT	Contact Insertion/Extraction Tool	7078-KIT, 7078-MTR, 7152-KIT, 7152-MTR	
2499-DIGIO	Digital I/O Expansion Module	SourceMeter instruments		Hand Crimping Tool for 7078-KIT,		
2500INT-SMA	SMA Connector	2500INT integrating sphere	7078-HCT	7169-KIT	7078-KIT	
2500INT-FC/PC	FP/PC Connector	2500INT integrating sphere	7078-KIT	Connector Kit	7071, 7071-4, 7074-D, 7078-MTR	
2500INT-FC/APC 2600-IAC	FP/APC Connector Safety Interlock Adapter Connector	2500INT integrating sphere 2611, 2612, 2635, 2636, 2611A, 2612A,	7078-MTR	Mass Terminated Receptacle, Bulkhead Mount	7071, 7071-4, 7078-KIT, 7078-MTC	
	Screw Terminal Connector with	2635A, 2636A 2601, 2602 (2 needed), 2611, 2612 (2	7078-TRX-BNC	3-slot Male Triax to BNC Adapter	486, 487, 4210-CVU, 4801, 6514, 6517A, 6517B, 7072, 7072-HV	
2600-KIT	Strain Relief and Cover	needed), 2601A, 2602A (2 needed), 2611A, 2612A (2 needed) 2601, 2602 (2 needed), 2611, 2612 (2	7078-TRX-GND	3-slot Male Triax to BNC Adapter (guard removed)	237, 4200-SCS, 4801, 6517A, 6517B, 7051, 7072, 7072-HV, Series 2600,	
2600-TRIAX	3-Lug Triax Adapter	needed), 2601A, 2602A (2 needed), 2611A, 2612A (2 needed)	7078-TRX-TBC	3-Lug Female Triax Bulkhead	Series 2600A 7078-TRX cables	
3706-BKPL	Analog Backplane Extender Board	3706	,0,0 1111 120	Connector w/Cap	, 0, 0 1111 cubico	
3720-ST	Screw Terminal Block	3720	7152-HCT	Hand Crimp Tool for 7152-KIT, 7152-MTR	7152-KIT, 7152-MTR	
3721-ST	Screw Terminal Block	3721	7152-KIT		7152, 7152-MTR	
3723-ST	Screw Terminal Block	3723	/1)2-КП	-		
3723-ST-1	Screw Terminal Block	3723	7152-MTR	6-Position M-Series Receptacle w/Sockets	7152, 7152-KIT, 7152-MTC-2, 7152-MTC-10	
3724-ST	Screw Terminal Block	3724	7703-306A	DB50 Male Connector Kit	7701, 7703, 7705, 7709	
3730-ST	Screw Terminal Block	3730	7709-308A	DB25 Male Connector Kit	7701, 7707, 7709	
3731-ST 3740-ST	Screw Terminal Block Screw Terminal Block	3731 3740	7712-SMA-N	Female SMA to Male N-Type Adapter		
3750-ST	Screw Terminal Block	3750	7755	$50\Omega$ Feed-Through Terminator	RG 58 cable, 776, 3390	
3790-KIT50-R	50-pin Female D-sub Connector Kit			-	7703, 7705, 77XX, modules with	
3791-CIT	Contact Insertion and Extraction Tool	3720, 3722, 3723	7788	50-pin D Subconnector Kit	D sub connectors	
3791-KIT78-R	78-pin Female D-sub Connector Kit	3720, 3723, 3724	7789	50-pin Male and 25-pin Male D-Shell Connector Kit	7701, 7709	
3792-KIT104-R	104-pin Male D-sub Connector Kit	3722		50-pin Male, 50-pin Female, and 25-pin Male IDC D-Shell	7701, 7703, 7705, 7707, 7709	
3792-KIT104-R/F	104-pin Female D-sub Connector Kit		7790			
4851	BNC Shorting Plug	Instruments with BNC connectors	Connector Kit			
6171	3-slot Male to 2-Lug Female Triax	2-lug triax connectors	8610	Low Thermal Shorting Plug	2000, 2001, 2002, 2010 2000, 2001, 2002, 2010, 2015, 2016,	
	Adapter 2-slot Male to 3-Lug Female Triax	U	8620	4-Wire DMM Shorting Plug	Series 2400, Series 2700, Series 3700	
6172	Adapter	7065, 2500INT	8680	RTD Probe Adapter	2001, 2002, 2010	




Model	Name	Use With:
BG-18	Dual Banana to BNC Coaxial Adapter	230, Series 2000, Series 2400, 2700, 2750
CAP-18	Protective Shield/Cap	BNC, 2-lug triax connectors
CAP-31	Protective Shield/Cap	3-lug triax connectors
CS-400	DB25 Male Solder Cup	CA-126-1 cable, 213
CS-458	Interlock Connector Kit	6517-ILC-3
CS-565	BNC Barrel, 4200-SCS	BNC interconnect
CS-630	3-Lug Female Triax Bulkhead Connector	6487, 6517A, 6517B
CS-631	3-Lug Male Triax Cable Mount Connector	4200-SCS, SC-22 cable
CS-701	BNC Tee Adapter (Female-Male- Female)	4200-SCS
CS-719	3-Lug Triax Jack Receptacle	4200-SCS
CS-846	Screw Terminal Test Lead Connector	230X, 2510, 2510-AT
CS-970	High Voltage Bulkhead Connector	248, 248-SHV cable

Model	Name	Use With:
CS-1247	SMA Female to BNC Male Adapter	4200-SCS
CS-1249	SMA Female to SMB Plug Adapter	4200-SCS
CS-1251	BNC Female to SMB Plug Adapter	4200-SCS
CS-1252	SMA Male to BNC Female Adapter	4200-SCS
CS-1281	SMA Female to SMA Female Adapter	4200-SCS
CS-1305	Interlock Connector	6517B
CS-1382	Female MMBX Jack to Male SMA Plug Adapter	4200-SCS
CS-1390	Male LEMO Triax to Female SMA Adapter	4200-SCS
CS-1391	SMA Tee Adapter (Female-Male- Female)	4200-SCS
CS-1423-3	Miniature Mating Connector	2635, 2636, 2635A, 2636A
CS-1479	SMA Male to BNC Male Adapter	4200-SCS
TL-24	SMA Torque Wrench	4200-SCS, System 46, System 46T



**Model 213-CON Analog Output Connector:** Quick disconnect analog output connector for Model 213 Quad Voltage Source. Screw terminals provided for connection of test leads.

### For use with: Instruments with 12-pin analog connectors



**Model 237-BAN-3A Triax to Banana Plug:** Triax cable center conductor terminated in a safety banana plug (guard and shield open). For connecting DMMs and other banana jack instruments to a matrix or fixture.

For use with: 4200-SCS, 7072, 7072-HV, DMMs



**Model 237-BNC-TRX:** Male BNC to 3-lug female triax adapter (guard disconnected). Terminates triax cable in BNC plug. High voltage rating for use with 237 and 7072-HV.

### For use with: 237, 4200-SCS, 6517A, 6517B, 7078-TRX cables



**Model 237-TRX-BAR:** 3-lug triax barrel (female to female) for use with triax interconnect.

For use with: 2635, 2635A, 2636, 2636A, 4200-SCS, triax interconnect



**Model 237-TRX-NG:** 3-slot triax to 3-lug female triax adapter (guard removed) for non-guarded measurements. High voltage rating for use with 237, 7072-HV, etc.

For use with: 237, 6517A, 6517B, 7072, 7072-HV



**Model 237-TRX-T:** 3-slot male to dual 3-lug female triax tee adapter for use with 7078-TRX cables and 7072/7072-HV Semiconductor Matrix Cards. High voltage rating for use with Models 237 SMU and 6517B Electrometer.

For use with: 237, 4200-SCS, 6517A, 6517B, 7072, 7072-HV, 7078-TRX cables

Connectors, adapters, and tools





**Model 237-TRX-TBC:** 3-lug female triax bulkhead connector with cap for assembly of custom panels and interface connections. High voltage rating for use with 237, 7072-HV, etc. Uses miniature coax cable, not triax cable, at soldered end. Bulkhead is outer shield.

For use with: 7072, 7072-HV, 7078-TRX cables

**Model 2182-325A:** Silver solder for making connections in experiments with the Model 2182A. 20 ft roll.

#### For use with: 2182A



Model 2182-KIT Low-Thermal Connector with Strain Relief: Connector kit for building a custom input cable for the Model 2182A Nanovoltmeter. Includes a low-thermal (LEMO) connector and a strain relief.

For use with: 2182A, SC-93



Model 2188 Low-Thermal Calibration Shorting Plug: A low-resistance, low-thermal shorting plug required to calibrate the Model 2182A Nanovoltmeter. Made of a LEMO connector with its pin connectors shorted together using copper wire and Sn/Ag4 silver solder.

#### For use with: 2182A



**Model 2499-DIGIO:** Digital I/O expansion module that plugs onto the DB-9 connector of a SourceMeter<sup>®</sup> instrument. Expands the three digital I/O lines of the SourceMeter to 16 lines. The SOT, EOT/BUSY, 5V, GND, and Interlock signals are passed through.

**Services Available:** 1-year factory warranty extended to 3 years from date of shipment

For use with: SourceMeter Instruments

Model 2500INT-FC/ APC: FC/APC connector for 2500-INT Integrating Sphere.

For use with: 2500-INT

Model 2500INT-FC/ PC: FC/PC connector for 2500-INT Integrating Sphere.

For use with: 2500-INT

Model 2500INT-SMA: SMA connector for 2500-INT Integrating Sphere. For use with: 2500-INT










Model 2600-IAC: Safety interlock adapter connector.

For use with: 2611, 2612, 2635, 2636, 2611A, 2612A, 2635A, 2636A



**Model 2600-KIT:** Extra screw terminal connector, strain relief, and cover for a single SourceMeter channel (two needed for use with Models 2602, 2612, 2602A, and 2612A).

For use with: 2601, 2602, 2611, 2612, 2601A, 2602A, 2611A, 2612A







**Model 2600-TRIAX:** Triax adapter for a single Series 2600 or 2600A SourceMeter channel (two needed for use with Models 2602, 2602A, 2612, and 2612A). For use with standard 3-lug triax cables.

### For use with: 2601, 2602, 2611, 2612, 2601A, 2602A, 2611A, 2612A




**Model 3721-ST:** Screw Terminal Block. Required with the Model 3721 for automatic CJC thermo-couple measurements.






Model 3724-ST: Screw Terminal Block. For use with: 3724



Model 3730-ST: Screw Terminal Block. For use with: 3730



Model 3731-ST: Screw Terminal Block. For use with: 3731

ACCESSORIES



**Model 3706-BKPL:** Analog backplane extender board, 15-pin D-sub to terminal block.

### For use with: Series 3700



**Model 3720-ST:** Screw Terminal Block. Required with the Model 3720 for automatic CJC thermocouple measurements.

For use with: 3720



**Model 3723-ST:** Screw Terminal Block. Accessory for Model 3723 for two-pole applications.

For use with: 3723



**Model 3723-ST-1:** Screw Terminal Block. Accessory for the Model 3723 for single-pole applications.

For use with: 3723








**Model 3732-ST-C:** Screw Terminal Block. Enables screw terminal access and additional matrix sizes including: quad 4×28 (1W), dual 4×28 (2W), single 4×56 (2W), dual 4×56 (1W), and single 4×112 (1W).

### For use with: 3732



**Model 3732-ST-R:** Screw Terminal Block. Enables screw terminal access and additional matrix sizes including: dual 8×28 (1W), single 8×28 (2W), and single 16×28 (1W).

### For use with: 3732



Model 3740-ST: Screw Terminal Block. For use with: 3740



Model 3750-ST: Screw Terminal Block. For use with: 3750



**Model 3790-KIT50-R:** 50-pin female D-sub connector kit that contains two female D-sub connectors and 100 solder cup contacts. Use for assembly of custom cable and harnesses compatible with Series 3700 plug-in cards.

### For use with: 3721, 3730, 3731, 3740, 3750



**Model 3791-CIT:** Contact insertion and extraction tool for assembly and maintenance of Series 3700 D-sub Connector kits.

For use with: 3791-KIT78-R, 3791-KIT104-R



**Model 3791-KIT78-R:** 78-pin female D-sub connector kit that contains two female D-sub connectors and 156 solder-cup contacts. Use for assembly of custom cable and harnesses compatible with Series 3700 plug-in cards.

For use with: 3720, 3723, 3724



**Model 3792-KIT104-R:** 104-pin male D-sub connector kit that contains two male D-sub connectors with housings and 208 solder-cup contacts. Use for assembly of custom cable and harnesses compatible with Series 3700 plug-in cards.

### For use with: 3722



**Model 3792-KIT104-R/F:** 104-pin female D-sub connector kit that contains two female D-sub connectors with housings and 208 solder-cup contacts. Use for assembly of custom cables, harnesses, and DUT interface compatible with Series 3700 plug-in cards.

For use with: 3722



ACCESSORIES



Model 4851: BNC shorting plug. For use with instruments with BNC connectors




**Model 6171:** 3-slot male to 2-lug female triax adapter.

#### For use with: 2-lug triax connectors



**Model 6172:** 2-slot male to 3-lug female triax adapter. For use in adapting Models 7065 and 250INT inputs to 3-slot triax plugs.

#### For use with: 7065, 2500INT



**Model 7001-PNL:** Metal plate used to cover an empty card slot on the rear panel of a Model 7001.


For use with: 7001

1.888.KEITHLEY (U.S. only) www.keithley.com




**Model 7011-KIT-R:** 96-pin female DIN connector with solder eyelets and strain relief. This kit can be used for assembly of custom cables to connect with the connectors on the 7011-C, 7012-C, 7013-C, 7015-C, and 7018-C switch cards. Also connects with the 7011-MTR bulkhead mount male connector.

For use with: 7011-C, 7012-C, 7013-C, 7015-C, 7018-C




**Model 7011-MTR:** 96-pin male DIN connector with solder eyelets for bulkhead mount. Connects with the 7011-KIT-R and the 7011-MTC-2.

For use with: 7011-KIT-R, 7011-C, 7012-C, 7013-C, 7015-C, 7018-C




**Model 7011-ST:** Extra quick disconnect screw terminal board. One 7011-ST is included with each 7011-S.

For use with: 7011-S




**Model 7012-ST:** Extra quick disconnect screw terminal board. One 7012-ST is included with each 7012-S.

For use with: 7012-S



**Model 7013-ST:** Extra quick disconnect screw terminal board. One 7013-ST is included with each 7013-S.

For use with: 7013-S




**Model 7014-ST:** Extra quick disconnect isothermal screw terminal board with cold junction sensor. One 7014-ST is included with each 7014.

For use with: 7014

Connectors, adapters, and t<u>ools</u>






**Model 7015-ST:** Extra quick disconnect screw terminal board. One 7015-ST is included with each 7015-S.


For use with: 7015-S

Connectors, adapters, and tools




**Model 7018-ST:** Extra quick disconnect screw terminal board. One 7018-ST is included with each 7018-S.





**Model 7072-TRT:** Triax removal tool used to connect or disconnect triax style connectors when clearance is limited making it difficult to mate or unmate a connector with your fingers.

For use with: 707B, 708B



**Model 7074-CIT:** Contact extraction tool for removal of contacts from cables and connectors.

For use with: 7152-KIT, 7152-MTR



Model 7074-HCT: Contact crimping pliers for assembly of cables and connectors.

For use with: 7152-KIT, 7152-MTR




**Model 7078-CIT:** Contact insertion and extraction tool for assembly and maintenance of 7078-MTC cables and connectors.

For use with: 7078-KIT, 7078-MTR, 7152-KIT, 7152-MTR




**Model 7078-HCT:** Contact crimping pliers for assembly of cables and connectors using 7078-MTR or 7078-KIT.

#### For use with: 7078-KIT



**Model 7078-KIT:** 38-pin male plug assembly with strain relief and 40 contacts for assembly of custom cable and harnesses compatible with Model 7071 8×12 Matrix Card, Model 7071-4 Dual 4×12 Matrix Card, and 7078-MTR Mass Terminated Receptacle. Requires 7078-HCT; recommend 7078-CIT.

For use with: 7071, 7071-4, 7074-D, 7078-MTR



**Model 7078-MTR:** 38-pin female bulkhead mount receptacle with 40 contacts for custom interface and patch panels compatible with 7078-MTC and 7078-KIT. Requires 7078-HCT; recommend 7078-CIT.

For use with: 7078-KIT, 7078-MTC, 7071, 7071-4



ACCESSORIES





**Model 7078-TRX-BNC:** 3-slot male triax to BNC adapter for use with 7072 Semiconductor Matrix Card and 4801 cables.

For use with: 486, 487, 4210-CVU, 4687, 4801, 6514, 6517A, 6517B, 7072, 7072-HV



**Model 7078-TRX-GND:** 3-slot male triax to female BNC adapter (guard removed) for adapting non-guarded measurements to the Model 237 SMU, 7072 or 7072-HV Semiconductor Matrix Cards, or 8006 or 8008 Test Fixtures.

### For use with: 237, Series 2600, Series 2600A, 4801, 6517A, 6517B, 7051, 7072, 7072-HV




**Model 7078-TRX-TBC:** 3-lug female triax bulkhead connector with cap for assembly of custom panels and interface connections.

For use with: 7078-TRX Cables



**Model 7152-HCT:** Contact crimping pliers for assembly of cables and connector using 7152-MTR or 7152-KIT.

For use with: 7152-KIT, 7152-MTR



**Model 7152-KIT:** 6-pin plug assembly with strain relief and contacts for assembly of custom cable and harnesses compatible with Model 7152 4×5 Low Current Matrix Card and 7152-MTR Mass Terminated Receptacle. Requires 7152-HCT recommend 7074-CIT and 7074-HCT.

For use with: 7152, 7152-MTR



**Model 7152-MTR:** 6-pin bulkhead mount receptacle with contacts for custom interface and patch panels compatible with 7152-MTC and 7152-KIT. Requires 7152 HCT; recommend 7074-CIT and 7074-HCT.

For use with: 7152, 7152-KIT, 7152-MTC-2, 7152-MTC-10



**Model 7703-306A:** DB50 male connector kit (solder cup) with shell.

For use with: 7701, 7703, 7705, 7709



**Model 7709-308A:** DB25 male connector kit (solder cup) with shell.

For use with: 7701, 7707, 7709



**Model** 7712-SMA-N: Female SMA to male N-type adapter.

For use with: 7711, 7712

Connectors, adapters, and tools





Model 7755 50Ω Feed-Through Terminator: BNC-to-BNC adapter for terminating RG58 cable in its characteristic impedance. VSWR <1.1, DC-250MHz.

For use with: RG58 Cable, 776, 3390



Model 7790: 50 pin male, 50 pin female, 25 pin male IDC D-Shell Connector Kit (one each).

For use with: 7701, 7703, 7705, 7707, or 7709 Integra modules



Model 7788: 50-pin D subminiature connector kit. To mate with 50-pin connector on Model 7703 and 7705.


#### For use with: 7703, 7705, 77XX modules with D sub connectors



Model 7789: 50-pin/25-pin (both male) D-Shell Kit (one of each) for 7701 or 7709 Integra modules (mating connectors are supplied with these modules when purchased).




Connectors, adapters, and tools





Model 8610 Low Thermal Shorting Plug: For calibration lab use, this plug provides a very low thermal offset short at front or rear inputs.

### For use with: 2000, 2001, 2002, 2010



Model 8620 Four-Wire DMM Shorting Plug: Provides a low resistance 4-wire short to both observe and cancel DMM offset resistances and voltages to improve measurement accuracies.

For use with: 2000, 2001, 2002, 2010, 2015, 2016, Series 2400, Series 2700, Series 3700



Model 8680 RTD Probe Adapter: Provides a means of connecting RTD probes terminated in either a 4-wire instrumentation connector or bare wires to safety input jacks on a 0.5 inch spacing. Use with Models 8681, 8693, 8695, or 8696.

For use with: 2001, 2002, 2010



BG-18: Dual banana to BNC coaxial adapter for adapting connection on instrument with dual banana jack.

For use with: 230, Series 2000, Series 2400, 2700, 2750



CAP-18: Protective shield/cap for BNC connectors. For use with: BNC connectors







**CAP-31:** Protective shield/cap for 3-lug triax connectors.

For use with: 3-lug triax connectors



CS-400: DB25 male solder cup. For use with: C126-1 cable, 213



**CS-458:** Interlock connector kit to mate with 6517-ILC-3.

For use with: 6517-ILC-3



CS-565: Female BNC to female BNC adapter with  $50\Omega$  nominal impedance. For use with: 4200-SCS, BNC interconnect



CS-630: 3-lug female triax bulkhead connector for soldered connection. Mates with CS-631. For use with: Fixtures, 6487, 6517A, 6517B



**CS-631:** 3-slot male triax cable mount connector for use with SC-22 cable. Mates to Models 237, 486, 487, 7072, and 8006.

For use with: 4200-SCS, SC-22 cable



**CS-701:** BNC tee adapter (female, male, female). **For use with: 4200-SCS** 



CS-719: 3-lug triax jack receptacle. For use with: 4200-SCS



CS-846: Eight position connector with screw terminals for connection to test leads. For use with: 230X, 2510, 2510-AT



CS-970: High voltage bulkhead connector. For use with: 248, 248-SHV cable





A GREATER MEASURE OF CONFIDENCE



CS-1247: SMA female to BNC male adapter For use with: 4200-SCS



CS-1249: SMA female to SMB plug adapter For use with: 4200-SCS



CS-1251: BNC female to SMB plug adapter For use with: 4200-SCS



CS-1252: SMA male to BNC female adapter For use with: 4200-SCS



CS-1281: SMA female to SMA female adapter For use with: 4200-SCS



CS-1305: Interlock connector to mate with Model 6517B.

For use with: 6517B



CS-1382: Female MMBX jack to male SMA plug adapter with  $50\Omega$  impedance and 6GHz maximum frequency For use with: 4200-SCS



CS-1390: Male LEMO triax to female SMA adapter For use with: 4200-SCS



CS-1391: SMA tee adapter (female-male-female) For use with: 4200-SCS



**CS-1423-3:** Miniature mating connector used as a ground connector for the Models 2635, 2635A, 2636, and 2636A.

### For use with: 2635, 2636, 2635A, 2636A



CS-1479: SMA male to BNC male adapter For use with: 4200-SCS



TL-24: SMA torque wrench For use with: 4200-SCS, System 46, System 46T





### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - Between Series category:

Click to view products by Keithley manufacturer:

Other Similar products are found below :

 R191203007
 R191209000
 R191212000
 R191215000
 R191301000
 R191325000
 R191403000
 R191405000
 R191416000

 R191419000
 R191421000
 R191424000
 R191445000
 R191511000
 R191552000
 R191720000
 R191733000
 R191759000

 R191841001W
 R191911000
 R191912000
 R191968001W
 R192417010
 R921390000
 ADBJ20-E1-BJ379
 ADM2
 ADPL75-A1-PL75

 ADPL75-E1-UBJ20
 9317505
 931RPBUFLP
 AD130
 ADBJ20-E1-PL74
 ADBJ20-E2-BJ79
 ADBJ77-A1PL3155
 ADBJ77-E1-UPL20

 ADBJ77-E2-PL20
 242215
 242228
 CP-AD851
 R125680000W
 R191117000
 R191123000
 R191303000
 R191313000

 R191315000
 R191316700
 R191327000
 R1913123000
 R191316700
 R191327000