

Keysight Technologies

82357B USB/GPIB Interface for Windows

Data Sheet



Features

- Fast and easy connection to GPIB instruments
- Uses standard USB interface
- Interface with up to 14 GPIB instruments
- IEEE-488 compatible
- Transfer over 1.15 MB/s with large block transfers
- Uses industry standard software
- Parallel polling capability



The Fastest and Easiest Connection

Gain the ultimate speed and efficiency by connecting your PC or laptop to your test and measurement instruments. The Keysight Technologies, Inc. 82357B USB/GPIB Interface provides direct connection from the USB port of your PC to GPIB Instruments.

USB (Universal Serial Bus) is built into most of today's desktop and laptop computers, offering fast and easy plug-and-play connection and auto configuration. Furthermore, the 82357B USB/GPIB Interface makes connectivity easier as there are no switches to set, and no PC cards to install.

Getting connected has never been easier with the 82357B USB/GPIB Interface, thanks to automatic configuration and use of industry standards. Your applications will be up and running in an instant.

Totally Transparent, Fully Compatible

The USB/GPIB Interface software allows transparent communication between a PC and one or more GPIB instruments. The bundled VISA (Virtual Instrument Software Architecture) software provides GPIB emulation so that your existing GPIB programs work immediately, without any modification needed. You also do not need to learn a new programming language to make the connection.

USB support is standard in Windows XP/Vista/ Windows 7. These operating systems support the automatic plug-and-play configurations, thus it is easy to install, configure, and use the USB devices. Standard plug-and-play devices, like the 82357B are automatically detected as soon as they are connected to the computer's USB port.

This capability provides convenience and reduces setup time. It is also hot pluggable, making it easy to connect and disconnect without having to shut down the computer. No external power supplies are necessary.

Full Assurance for Interoperability

The USB/GPIB Interface comes with the Keysight I/O Libraries Suite that includes VISA and SICL. VISA enables interoperability among different instrument and software vendors. The IO Libraries Suite also provides robust instrument control and works with the software development of your choice.

Standard GPIB functionality is provided by implementing the IEEE 488.1 and IEEE 488.2 specifications. These specifications provide defined mechanical and electrical characteristics, and a basic set of instrument commands and common data formats.

Using industry standards gives you the assurance and confidence that your programs will work with multiple hardware and software vendors, and migrate to new standards in the future.

Standard Computer IO

In the past, RS-232 and GPIB have been the primary interfaces used for connecting instruments to PCs in test and measurement applications. Although RS-232 offers a low-cost solution, RS-232's lower baud rate and connection limitations are cumbersome and too slow for many of today's measurement needs.

GPIB has provided a high performance, cost effective, and also reliable solution for more than 25 years. Today, however, computers have fewer available IO slots, leaving engineers with little options but to use more expensive solutions such as industrial PCs.

With USB and LAN built into most of today's PCs, standard computer IO has evolved into a solution that is acceptable for automation and control of test and measurement instruments.

Early USB devices that were initially developed for connecting PCs to peripherals such as keyboard, mouse and so forth offered little bandwidth. Today, USB offers bandwidths up to 12 Mbits/s for USB 1.1 and 480 Mbits/s for USB 2.0. The 82357B USB/GPIB Interface runs at USB 2.0.

The 82357B USB/GPIB Interface uses a thin, flexible, high-quality USB cable that is USB 1.1 and 2.0 compliant. This cable is shielded and specified to 1,500 insertions, ensuring a durable connection and reliable data transfer.

The 82357B is capable of transfer rates over 1.15 MB/s with large block transfers. The performance is better

than typical GPIB cards for block sizes over 32KB. Small block transfers are limited by the USB implementation and the overhead associated with setting up the transfer. However, since instrument setup time can dominate the overall test time, this impact may be minimal.

If small block transfer performance is critical, then you may consider the Keysight 82350A PCI GPIB interface.

Make the Connection

You may connect directly to one instrument with no additional GPIB cables required with the 82357B USB/GPIB Interface.

For multiple instruments connection, use a daisy chain or star configuration with your GPIB instruments using standard GPIB cables. Once the instruments are connected, connect the USB/GPIB Interface as the last connection on one of the instruments. One 82357B USB/GPIB Interface supports up to 14 GPIB instruments. Multiple 82357B USB/GPIB Interfaces can be connected to improve system performance.

Another additional significant feature would be the parallel polling capability of the 82357B USB/GPIB Interface. This allows you to easily check up to eight individual devices at once, corresponding to the number of data lines on the GPIB.



Software Included

The VISA standard is a system-level industry standard supported by a multi-vendor foundation for instrument software. It offers an easy-to-use set of IO control functions and provides a migration path to new standards such as IVI (Interchangeable Virtual Instruments). IVI is a new driver standard developed by instrument and software vendors to define software standards for instrument interchangeability. This new standard is layered on Keysight VISA and offers interchangeability and high performance.

The Interactive IO software is also included and it provides utility for sending commands and queries to an instrument to help view the response returned by the instrument.

Take a Look for Yourself

To see the 82357B USB/GPIB Interface in action, check out the demo at www.keysight.com/find/82357B.

Ordering Information

82357B USB/GPIB Interface for Windows

Options

Option 0B1 – Add Paper Manual Set

Accessories

None

For more information on Keysight GPIB and instrument control products, visit www.keysight.com/find/gpib.

Technical Specifications

General Requirements

Minimum system requirements			
Operating System	Microsoft Windows XP Service Pack 3 (or later)	Microsoft Windows Vista SP1 and SP2 (32-bit and 64-bit), Business, Ultimate, Enterprise, Home Basic, and Home Premium	Microsoft Windows 7 (32- and 64-bits), Home Basics, Home Premium, Professional, Ultimate, Enterprise
Processor	600 MHz Pentium II or higher required. 800 MHz recommended	1 GHz 32-bit (x86), 1 GHz 64-bit (x64)	1 GHz 32-bit (x86), 1 GHz 64-bit (x64)
Available memory	256 MB minimum (1 GB or greater recommended)	1 GB minimum	1 GB minimum
Available hard disk space*	1.5 GB available hard disk space includes: – 1 GB available for Microsoft .NET Framework 2.0 – 65 MB for Keysight IO Libraries Suite	1.5 GB available hard disk space includes: – 1 GB available for Microsoft .NET Framework 2.0 – 65 MB for Keysight IO Libraries Suite	1.5 GB available hard disk space includes: – 1 GB available for Microsoft .NET Framework 2.0 – 65 MB for Keysight IO Libraries Suite
Video	Super VGA (800x600) 256 colors or more	Support for DirectX 9 graphics with 128 MB graphics memory recommended (Super VGA graphics is supported)	Support for DirectX 9 graphics with 128 MB graphics memory recommended (Super VGA graphics is supported)
Browser	Microsoft Internet Explorer 5.01 or greater	Microsoft Internet Explorer 7 or greater	Microsoft Internet Explorer 7 or greater
		Support USB 2.0 high speed and full speed – Standard USB endpoints supported – IEEE-488.1 and IEEE-488.2 compatible – SICL and VISA 2.2	

Supported Languages and Applications

Applications (with Intui Link)	<ul style="list-style-type: none">– Microsoft Excel 97 and 2000– Microsoft Word 97 and 2000– Check the Web for latest supported applications
Software development applications	<ul style="list-style-type: none">– Keysight VEE 6.0 or greater– Visual Basic 6.0– Visual C++ 6.0– Visual Studio .NET– BASIC for Windows– LabVIEW 6.0 or greater

General Characteristics

Power	USB bus-powered device, +5 V, 500 mA(max), 200 mA(typ)
GPIB transfer rate	1.15 MB/s or better
Connectors	Standard 24-pin IEEE-488, Standard USB A
USB Hubs	Self-powered hubs
Parallel polling	A single parallel poll can check up to 8 individual devices at once, corresponding to the number of data lines on the GPIB.
Dimensions	105 mm (L) x 64 mm (W) x 30 mm (H) (includes connectors)
Weight	215 grams
Cable	2.5 meters, shielded, connector rated for 1500 insertions
LED Indicators	Ready, Access, Fail
Maximum connections	Maximum 4 converters can be connected to the PC
Instrument connection	14 instruments – daisy chain via GPIB
Configuration	Plug-and-play

Environmental Specifications


Operating environment	0 °C to 55 °C
Storage environment	– 40 °C to +70 °C
Operating humidity	Up to 90 % at 40 °C non-condensing
Storage humidity	Up to 90 % at 65 °C non condensing

NOTE: If possible, you should always use the current version of the Keysight IO Libraries (spacing) Suite. This version supports the newest interfaces and operating systems, and has the most advanced features. The Keysight 82357B USB/GPIB Interface is supported for PCs with Windows XP Professional, Windows Vista or Windows 7 operating systems only. However, you may need an earlier version of the IO Libraries Suite to support an older interface or operating system. If you need an earlier version of Keysight IO Libraries, go to <http://www.keysight.com/find/iosuite> to locate the version you need.

Evolving Since 1939

Our unique combination of hardware, software, services, and people can help you reach your next breakthrough. We are unlocking the future of technology.

From Hewlett-Packard to Agilent to Keysight.



myKeysight

myKeysight

www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.

http://www.keysight.com/find/emt_product_registration

Register your products to get up-to-date product information and find warranty information.

KEYSIGHT SERVICES

Accelerate Technology Adoption.
Lower costs.

Keysight Services

www.keysight.com/find/service

Keysight Services can help from acquisition to renewal across your instrument's lifecycle. Our comprehensive service offerings—one-stop calibration, repair, asset management, technology refresh, consulting, training and more—helps you improve product quality and lower costs.



Keysight Assurance Plans

www.keysight.com/find/AssurancePlans

Up to ten years of protection and no budgetary surprises to ensure your instruments are operating to specification, so you can rely on accurate measurements.

Keysight Channel Partners

www.keysight.com/find/channelpartners

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at:

www.keysight.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 11 2626
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

Europe & Middle East

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:

www.keysight.com/find/contactus
(BP-9-7-17)

DEKRA Certified
ISO 9001 Quality Management System

www.keysight.com/go/quality

Keysight Technologies, Inc.
DEKRA Certified ISO 9001:2015
Quality Management System



This information is subject to change without notice.
© Keysight Technologies, 2017
Published in USA, December 2, 2017
5989-5983EN
www.keysight.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Keysight](#) manufacturer:

Other Similar products are found below :

[65-647-8-BK-BU](#) [950](#) [952](#) [E8144-B01021-L](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBD11135](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [17-210051](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SMT-AS1N-W30](#) [4689-1](#) [1-1734084-2](#) [E8110-001-01](#) [33UBARS1-04SW11](#) [33UBAR-04SW11](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [10135326-001LF](#) [M9177/3-1](#) [USB-A-S-F-B-VT](#) [925](#) [4198](#) [690-024-633-031](#) [KUSBEX-BSFS1N-W](#) [USBFTVC6MRG](#) [UA-20BMFA-SL8001](#) [17-250101](#)