

NOTE:

- 1. HEAT TREAT TO SPRING TEMPER
- 2. DESIGNED TO CLIP OVER PANELS FROM .060 [1.52] THRU .070 [1.78] THK.
- * DENOTES $\pm .015$ [$\pm .38$] TOLERANCE

ယ



THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

ACTUAL SIZE

KEYSTONE ELECTRONICS CORP.

www.keyelco.com ◆ NEW HYDE PARK, NY 11040 ◆ Tel (516) 328-7500 PART NAME

DUAL 'A' - 'AA' CONTACT

MATERIAL
.012 [0.30] TH'K ANNEALED SPRING STEEL

O12 [0.30] IH'K ANNEALED SPRING STEEL

| DRING BOONE | DATE | 12.9.82

NICKEL PLATE

NICKEL PLATE

APPD

TOLERANCES INCH [MM] CODE DWG NO.

ANGULAR ± 1°

UNLESS OTHERWISE SPECIFIED

NICKEL PLATE

APPD

SCALE 3X

DEGINAL ± .010 [± 0.25] C

210

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cylindrical Battery Contacts, Clips, Holders & Springs category:

Click to view products by Keystone manufacturer:

Other Similar products are found below:

753-00001 12BH36A-GR 200 183 270 QX3506 5220 5230 1055 1088 5250 166 591 1044 KT0008 1119 254TR 5207 1121 246
4027003022001-PK 1012 1020 1024 1024C 1075 1077 1080 1088 1090 1096 1097 1098 1109 1126 1127 1128 1162 1173 147 148
150 151 152 153 154 155 169 171 175