









Notes:

Shell: Mat'l: Steel,

Insulator: Mat'l- Glass Filled LCP Finish: Nickel plate, over Copper

Contacts: Matl: Copper Alloy

Finish: Contact Area -Gold Plate over Nickel Plate Solder Tail - Tin Plate over Nickel Plate

> **Electrical Specifications** Rated Voltage: 30V AC (rms)

Contact Current Rating: 1A Max.

Dielectric Withstanding: 750V AC Contact Resistance: 30 milliohms Max

Operating Temperature: -55°C to 85°C

ACTUAL SIZE

KEYSTONE ELECTRONICS CORP.

405 [10.28] |REF

— 517 [13 14]-

- 091 [2 30] DIAHOLE (4) PLS

RECEPTACLE OPENING MOUNTING DETAIL

224 [5 68]

0

107 [2 71]

210 [5.33]

098 [2.50]

.276 [7.00]

079 [2 00]

~ 036 [0.92] DIA HOLE (8) PLS

www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900

PART NAME **USB A-TYPE DUAL-HORIZONTAL SOCKET**

	MATERIAL	SNO	AS NOTED	
	FINISH		DRN BY NT	DATE 6.18.98
ı	AUNOIED		APP'D	SCALE 2X
,	TOLERANCES INCH [MM]	CODE	DWG NO	
	ANGULAR ± 1° UNLESS OTHERWISE SPECIFIED	С	922	2

UNLESS OTHERWISE S	FROM KEYSTONE ELECTRONICS CORP.
ANGULAR ± 1°	WITHOUT PRIOR WRITTEN PERMISSION
DECIMAL ± .0	SHALL NOT BE REPRODUCED, DISTRIBUTED OR LISED AS A BASIS FOR MANUFACTURE
TOLERANCES IN	THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Keystone manufacturer:

Other Similar products are found below:

65-647-8-BK-BU 950 E8144-B01021-L A-USB A-LP-SMT-C A-USB B-TOP-C MUSBA511N5 MUSBD11135 217450-1 CA 6 W LD KMBVX-TH-5S-B30 896-30-004-00-000000 KUSBVX-BS1N-W30 KUSBX-AP-KIT-SCBLK KUSBX-AS2N-W KUSBX-SMT2AP1S-W KUSBX-SMT2AP1S-W 6489-6 17-210051 1734082-1 30-1574 30-470 30-489 30-541 30-572-3 MAB 8 SN V A-USB A-2P-C MIKROE-1451 USBFTV2PEM2G USBFTVC6ZN KUSBX-AS2N-W30 KUSBX-SLAS1N-W KUSBX-SMT-AS1N-W30 4689-1 1-1734084-2 E8110-001-01 MUSBA81130 33UBARS1-04SW11 33UBAR-04SW11 USBF21ZNSCC USBBFTV6ZC 10135326-001LF M9177/3-1 USB-A-S-F-B-VT 925 4198 690-024-633-031 KUSBEX-BSFS1N-W USBFTVC6MRG