

RECEPTACLE OPENING

114 [2 90]

.098 [2.50]

079 [2.00] –

043 [1 10]

078 [1 99]

MOUNTING DETAIL **-**| 276 [7.00] |**-** 043 [1 10] DIA -HOLE (2) PLS

461 [11 70]—

181 [4 60]

- 035 [0 90] x 098 [2 50] (2) PLS

8.30.17 ECN 17-055, ADD INSULATOR COLOR

 \bigcirc

© WAS .240 [6.10]

12.05.14 CHANGE AS PER ECN 14-119 (B) WAS 4.50mm

12.21.09 CHANGE AS PER ECN 09-192

DESCRIPTION

REV.

 \triangleright

W

Contact Current Rating: 1 A max. Contact Resistance: 30 milliohms Max. Operating Temperature: -20°C to 85°C Dielectric Withstanding: 500V AC

Contact Area: Gold Plate over Nickel Plate

on Solder Tail: Tin Plate over Nickel Plate



Electrical Specifications
Rated Voltage: 30V AC (rms)

Notes:

Materiall:

Shell: Steel, Nickel Plate.

Contacts: Phosphor Bronze

Insulator: Glass Filled LCP (black color)

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED. DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN REPRINSSION FROM KEYSTONE ELECTRONICS CORP. ACTUAL SIZE

KEYSTONE ELECTRONICS CORP.

PART NAME www.keyelco.com ● NEW HYDE PARK, NY 11040 ● Tel (516) 328-7500

MATERIAL USB A-TYPE HORIZONTAL SMT PLUG

SCALE
DRN BY BOONE DATE & 31 OF

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Keystone manufacturer:

Other Similar products are found below:

65-647-8-BK-BU 950 E8144-B01021-L A-USB A-LP-SMT-C A-USB B-TOP-C MUSBA511N5 MUSBD11135 217450-1 CA 6 W LD KMBVX-TH-5S-B30 896-30-004-00-000000 KUSBVX-BS1N-W30 KUSBX-AP-KIT-SCBLK KUSBX-AS2N-W KUSBX-SMT2AP1S-W KUSBX-SMT2AP1S-W 6489-6 17-210051 1734082-1 30-1574 30-470 30-489 30-541 30-572-3 MAB 8 SN V A-USB A-2P-C MIKROE-1451 USBFTV2PEM2G USBFTVC6ZN KUSBX-AS2N-W30 KUSBX-SLAS1N-W KUSBX-SMT-AS1N-W30 4689-1 1-1734084-2 E8110-001-01 MUSBA81130 33UBARS1-04SW11 33UBAR-04SW11 USBF21ZNSCC USBBFTV6ZC 10135326-001LF M9177/3-1 USB-A-S-F-B-VT 925 4198 690-024-633-031 KUSBEX-BSFS1N-W USBFTVC6MRG