

KN series

- ◆ Load life 2000 Hrs at 105°C
- ◆ RoHS Compliant




Specifications 規格表

Ltem 項目	Performance Characteristics 特性參數	
Operating Temperature Range 工作溫度範圍	-40 to +105°C	-25 to +105°C
Rated Voltage Range 額定電壓範圍	16 to 100 VDC	160 to 500 VDC
Capacitance Range 容量範圍	68 to 56000 μ F	
Capacitance Tolerance 靜電容量偏差	$\pm 20\%$ (120Hz, +20°C)	
Leakage Current 漏電流	After 5 minutes at 20° C application of rated voltage, leakage current is not more than 0.01CV or 1.5mA, whichever is smaller C: Nominal Capacitance(μ F) V: Rated Voltage(V)	
Dissipation Factor 損耗角正切值 $\tan \delta$ (%)	rated voltage (V)	16 25 35 50 63 100 160-400 450-500
	$\tan \delta$ (Max)	50 40 40 30 20 20 15 20
Low Temperature Characteristics 低溫特性	impedance ratio max 電容器最大阻抗比值	
	rated voltage (V)	16 25 35 50 63 100 160-400 450-500
	Z(-25°C)/Z(+20°C)	4 4 4 4 4 4 4 8
	Z(-40°C)/Z(+20°C)	15 15 15 15 15 15 - -
Load Life 使用壽命	105°C施加額定工作電壓2000小時，經恢復後，產品性能應滿足以下要求 The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied for 2000H at 105°C	
	Capacitance change	$\cong \pm 20\%$ of the initial value
	D. F. ($\tan \delta$)	$\cong 200\%$ of the specified value
	Leakage current	\cong The specified value
Shelf Life 存儲特性	105°C放置1000小時，經恢復後20°C后，產品性能應滿足以下要求 The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1000 hours at 105°C without voltage applied.	
	Capacitance change	$\cong \pm 20\%$ of the initial value
	D. F. ($\tan \delta$)	$\cong 150\%$ of the specified value
	Leakage current	\cong The specified value

Diagram of Dimensions 外形尺寸圖 (mm)

●Standard Terminal Type : S ($\Phi 22 \sim \Phi 35$)



KN series

Frequency Coefficient

Frequency Voltage (v)	50/60 Hz	120 Hz	300 Hz	1K Hz	10K Hz	≥50K Hz
≤100V	0.95	1.00	1.07	1.13	1.19	1.20
160-250V	0.87	1.00	1.17	1.32	1.45	1.50
≥350	0.80	1.00	1.16	1.30	1.41	1.43

Standard Ratings

Rated Voltage V	Rated Capacity μF	Size φD*L mm	Rated ripple current A
16V	3300	22*26	1.17
		22*26	1.53
	4700	25*26	1.55
		22*31	2.02
	6800	25*26	2.02
		30*26	2.02
	8200	22*31	2.20
	10000	22*31	2.79
			25*26
		30*26	2.81
	12000	22*36	3.06
		30*26	3.06
	15000	22*41	3.24
			25*36
		30*26	3.24
			35*32
	18000	22*51	3.54
			25*46
		30*36	3.51
			35*32
	22000	25*51	4.25
			30*36
		35*32	4.08
	27000	25*51	4.30
30*41			4.30
33000	30*46	4.83	
		35*37	4.83
39000	30*51	5.78	
		35*42	5.78
47000	35*45	6.32	
56000	35*47	6.48	
25V	3300	22*26	1.48
		25*26	1.48
	4700	22*26	1.88
		25*26	1.90
	6800	22*31	2.60
		25*26	2.60
	8200	22*36	3.14
		25*31	3.14
	10000	30*26	3.14
			22*41
		25*36	3.50
	12000	30*31	3.50
			35*27
		22*46	4.02
	15000	25*41	4.02
			30*31
		35*27	4.02
	18000	25*46	4.58
			30*36
		35*32	4.58
	22000	25*51	4.82
			30*41
		35*32	4.79
	27000	30*46	5.12
35*37			5.12
27000	35*42	5.30	
33000	35*52	6.09	
39000	35*52	6.20	
47000	35*52	6.30	

Rated ripple current (A,rms) at 105°C, 120Hz

KN series

Standard Ratings

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current
V	μF	mm	A
35V	1500	22*26	1.26
	2200	22*26	1.35
		25*26	1.45
	2700	22*26	1.55
		25*26	1.65
	3300	22*26	1.80
		25*26	1.90
	4700	22*36	2.42
		25*26	2.30
		30*26	2.54
	6800	22*41	3.24
		25*36	3.24
		30*26	3.21
		35*27	3.24
	10000	25*46	3.96
		30*36	3.96
		35*27	3.75
	12000	25*51	4.21
		30*41	4.21
		35*32	4.21
15000	30*46	4.69	
	35*37	4.69	
22000	35*52	5.50	
27000	35*52	5.80	
	35*45	5.60	
33000	35*52	5.90	

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current
V	μF	mm	A
50V	1500	22*26	1.10
		25*26	1.02
	2200	22*31	1.65
		25*26	1.65
	2700	22*31	1.85
		25*26	1.85
		30*26	1.95
	3300	22*36	2.24
		25*31	2.24
		30*26	2.24
	4700	22*46	2.95
		25*36	2.80
		30*31	2.95
		35*27	2.95
	6800	25*46	3.23
		30*41	3.20
		35*32	3.26
	8200	30*46	3.58
		35*37	3.58
	10000	30*51	4.11
30*45		4.01	
35*42		4.11	
30*40		4.00	
25*50		3.90	
35*30		3.86	
15000	35*52	5.05	
18000	35*52	5.30	
22000	35*60	5.50	

Rated ripple current (A,rms) at 105°C, 120Hz

KN series

Standard Ratings

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current
V	μF	mm	A
63V	820	22*26	0.75
	1000	22*26	0.85
		25*26	0.85
	1500	22*26	1.10
		25*26	1.12
		30*26	1.14
	1800	22*31	1.40
		25*26	1.40
	2200	22*36	1.65
		25*31	1.65
		30*26	1.65
	2700	22*41	2.07
		25*36	2.07
		30*26	2.07
	3300	22*46	2.46
		25*36	2.40
		30*31	2.48
		35*27	2.48
	3900	25*41	2.92
		30*36	3.05
		35*27	3.05
	4700	25*51	3.43
		30*41	3.43
		35*32	3.43
	5600	30*46	3.86
		35*37	3.86
	6800	30*51	4.64
		35*42	4.64
	8200	35*47	5.05
	10000	35*52	5.75
30*60		5.65	
30*50		5.35	
15000	35*52	5.40	
	35*60	5.56	

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current
V	μF	mm	A
100V	330	22*26	0.54
	470	22*26	0.79
		25*26	0.81
	560	22*26	0.90
		25*26	0.95
	680	22*31	1.02
		25*26	1.02
		30*26	1.14
	820	22*31	1.26
		25*26	1.26
		30*26	1.32
	1000	22*36	1.38
		25*31	1.38
		30*26	1.38
	1200	22*41	1.65
		25*36	1.65
		30*31	1.65
	1500	22*46	1.83
		25*41	1.83
		30*31	1.83
		35*27	1.83
	1800	25*41	2.52
		30*36	2.52
		35*32	2.52
	2200	25*51	3.03
		30*41	3.03
		35*32	3.03
	2700	30*46	4.10
		35*37	4.10
	3300	30*56	4.59
35*47		4.59	
3900	35*47	4.98	
4700	35*52	5.03	
	35*40	4.80	
	30*50	4.65	
5600	35*60	5.10	
5600	35*52	5.09	
6800	35*60	5.20	

Rated ripple current (A,rms) at 105°C, 120Hz

KN series

Standard Ratings

Rated Voltage	Rated Capacity	Size ϕ D*L	Rated ripple current
V	μ F	mm	A
160V	220	22*26	0.42
	330	22*31	0.98
		25*26	0.98
		30*26	1.00
	470	22*36	1.21
		25*31	1.21
		30*26	1.21
		22*31	1.15
	560	22*41	1.40
		25*36	1.40
		30*31	1.40
		35*27	1.40
	680	22*46	1.64
		25*36	1.58
		30*31	1.65
		35*27	1.71
		22*36	1.49
	820	25*41	1.76
		30*36	1.85
		35*32	1.85
	1000	25*51	2.15
		30*41	2.15
		35*32	2.15
	1200	25*56	2.46
		30*46	2.46
		35*37	2.46
	1500	30*51	2.80
		35*42	2.80
1800	30*51	3.13	
	35*42	3.13	
2200	35*52	3.26	
	35*42	3.18	
3300	35*52	3.50	
	35*45	3.35	
200V	150	22*26	0.54
		25*26	0.54
	220	22*31	0.92
		25*26	0.92
		30*26	0.92
	270	22*31	1.03
		25*26	1.03
		30*26	1.05

Rated Voltage	Rated Capacity	Size ϕ D*L	Rated ripple current
V	μ F	mm	A
200V	330	22*36	1.21
		25*31	1.21
		30*26	1.21
	390	22*36	1.33
		25*31	1.34
		30*31	1.45
	470	22*41	1.57
		25*36	1.59
		30*31	1.65
		35*27	1.65
	560	22*30	1.55
		22*46	1.81
		25*41	1.85
		30*31	1.85
	680	35*27	1.85
		22*51	2.04
		25*46	2.07
		30*31	2.04
	820	35*32	2.17
		25*51	2.30
		30*36	2.30
	1000	35*37	2.31
		30*40	2.62
		35*37	2.62
	1200	25*45	2.55
		25*40	2.51
		35*30	2.50
		25*50	2.55
		30*30	2.45
	1500	30*35	2.51
		30*50	3.00
		35*42	3.00
1800	35*47	3.28	
	35*52	4.01	
2200	35*52	4.10	
	30*50	3.85	
2700	35*52	4.10	
	35*45	3.80	
250V	100	22*31	0.44
		25*26	0.44
	120	22*31	0.50
		25*26	0.50
	150	22*31	0.60
		25*26	0.60
		30*26	0.60
		30*26	0.60

Rated ripple current (A, rms) at 105°C, 120Hz

KN series

Standard Ratings

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current	
V	μF	mm	A	
250V	220	22*36	1.00	
		25*31	1.00	
		22*30	0.95	
	330	22*46	1.28	
		25*36	1.28	
		30*31	1.28	
	390	35*27	1.28	
		22*46	1.48	
		30*31	1.48	
	470	35*27	1.48	
		25*41	1.76	
		30*36	1.76	
	470	35*32	1.76	
		25*30	1.56	
		25*35	1.60	
		22*36	1.56	
		30*30	1.68	
		22*40	1.68	
	560	30*30	1.68	
		25*51	1.93	
		30*41	1.93	
	560	35*32	1.93	
		25*40	2.15	
		30*46	2.22	
	680	35*37	2.22	
		30*51	2.48	
		22*45	2.15	
		30*35	2.20	
	820	25*45	2.46	
		30*35	2.43	
		30*51	2.48	
		35*42	2.48	
		25*40	2.20	
	820	35*30	2.25	
		30*50	2.74	
		30*40	2.65	
		35*47	2.80	
	1000	30*45	2.70	
		1200	35*50	3.00
		35*55	3.00	
	1500	35*50	3.50	
		35*55	3.50	
2200	35*55	5.00		
	35*60	5.10		
	35*70	5.10		

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current	
V	μF	mm	A	
400V	100	22*36	0.82	
		25*31	0.82	
		22*25	0.70	
		25*25	0.80	
	120	22*36	0.90	
		25*31	0.90	
		22*25	0.80	
		25*25	0.85	
	150	22*41	0.98	
		25*36	0.98	
		30*31	0.95	
		35*27	0.95	
		22*30	0.90	
	150	25*25	0.90	
		180	25*36	1.05
	220	30*30	1.21	
		30*41	1.21	
		25*40	1.21	
		25*35	1.21	
		35*32	1.21	
		22*40	1.10	
		25*30	1.10	
	220	30*25	1.10	
		30*40	1.40	
		270	25*40	1.30
	270	30*35	1.30	
		330	30*40	1.57
	35*30		1.57	
	22*45		1.50	
	25*40		1.50	
	30*35		1.50	
	330	35*35	1.60	
		390	30*40	1.68
		35*42	1.71	
	390	35*45	1.94	
		25*50	1.80	
		30*40	1.80	
		470	35*35	1.80
			30*50	1.85
			30*45	1.85
		470	35*40	1.85
	35*50		1.98	
35*50	1.98			

Rated ripple current (A,rms) at 105°C, 120Hz

KN series

Standard Ratings

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current	
V	μF	mm	A	
400V	560	35*50	2.23	
		30*45	2.23	
		35*45	2.40	
		35*40	2.40	
	680	35*62	2.85	
		35*50	2.83	
		35*45	2.80	
		30*50	2.70	
	820	35*40	2.65	
		35*62	2.90	
		35*45	2.83	
	1000	35*50	2.85	
		35*70	3.20	
		35*65	3.15	
	1200	35*60	3.15	
		35*50	3.10	
		35*70	3.30	
	450V	82	35*70	3.30
			35*65	3.30
			35*60	3.30
100		22*36	0.64	
		25*31	0.64	
		30*26	0.64	
		22*41	0.74	
		25*31	0.74	
		30*31	0.74	
120		22*25	0.70	
		22*35	0.72	
		25*25	0.72	
		22*46	0.82	
		25*36	0.82	
		30*31	0.82	
		22*30	0.80	
150		25*25	0.80	
		25*30	0.80	
		30*25	0.80	
		22*51	0.96	
	25*41	0.96		
	30*36	0.96		
	150	35*27	0.96	
		22*30	0.90	

Rated Voltage	Rated Capacity	Size ΦD*L	Rated ripple current
V	μF	mm	A
450V	150	22*35	0.90
		25*30	0.90
		25*35	0.95
		30*25	0.95
		30*30	0.95
		25*46	1.14
	180	30*36	1.10
		35*32	1.14
		30*41	1.24
	220	35*37	1.24
		22*40	1.20
		25*40	1.20
		25*50	1.20
		30*30	1.20
	270	30*51	1.48
		35*42	1.48
	330	30*40	1.60
		30*50	1.64
		25*50	1.60
		30*35	1.60
		35*30	1.60
	390	35*40	1.80
		35*52	1.86
		35*35	1.65
	470	35*50	1.90
		35*45	1.90
		30*50	1.90
		30*60	1.90
	560	35*50	2.40
		35*45	2.40
		35*40	2.40
		30*50	2.40
680	35*60	2.90	
	35*50	2.85	
	35*45	2.80	
	30*55	2.80	
820	35*70	3.20	
	35*65	3.20	
	35*60	3.20	
1000	35*70	3.30	
	35*65	3.30	
1200	35*80	3.60	

Rated ripple current (A, rms) at 105°C, 120Hz

KN series

Standard Ratings

Rated Voltage	Rated Capacity	Size ϕ D*L	Rated ripple current
V	μ F	mm	A
500V	100	22*40	0.90
		22*45	0.94
		25*40	0.94
		30*30	0.94
	120	25*40	0.94
		30*30	0.94
		35*25	0.94
	150	25*40	1.10
		30*35	1.13
		35*30	1.13
	180	25*50	1.39
		30*40	1.40
	220	30*40	1.50
		30*45	1.60
		35*35	1.60
		35*40	1.60
	270	30*50	1.70
		35*40	1.70
	330	30*55	2.10
		30*60	2.10
		35*50	2.10
	390	35*55	2.50
		35*50	2.47
	470	35*55	2.60
		35*60	2.65
	680	35*70	3.10
	820	35*80	3.80
		40*70	3.80
1000	40*80	4.70	

Rated ripple current (A,rms) at 105°C, 120Hz

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - Snap In](#) category:

Click to view products by [KFSON](#) manufacturer:

Other Similar products are found below :

[NRLF103M25V35X20F](#) [EET-XB2W221LA](#) [LGQ2C681MELEDE](#) [108LMB200M2ED](#) [B41231C4229M](#) [LGM2W181MELA25](#) [MVK-25VC33-M-6.3*5](#) [ALC40F1012DH](#) [ALC40E1004EL](#) [LGZ2W151MELB40](#) [LGZ2W271MELC45](#) [LGZ2W221MELC40](#) [LGZ2W151MELC30](#) [LGZ2W121MELC25](#) [ALA8DA561EF500](#) [DCMC142T250AB2A](#) [ESMH630VSN123MA45U](#) [ESMH630VRT183MB50U](#) [E81D251VNN331MQ35U](#) [ELXS451VNN820MP25S](#) [ESMM181VSN402QA70U](#) [ELXG160VNN562MP25S](#) [ELXG160VSN562MP25S](#) [ESMH160VNN104MA80U](#) [450MXG82MEFCSN22X25](#) [EKMW421VSN391MQ45S](#) [KN821M25035*30C](#) [152EC0351](#) [152EC0343](#) [152EC0354](#) [TLS450V220M35*25](#) [KS200M821SI225*35TA-1B1ET](#) [KM450M101SI222*30TA-1A3ET](#) [400MXC220MEFCSN35X25](#) [TDA63V4700M22*50 V](#) [HP221M450N350AP4](#) [152EC0329](#) [LAO-50V103MS45PX#B](#) [152EC0566](#) [KN331M45035*30A](#) [KN821M45035*56P4](#) [450USC330MEFCSN25X50](#) [152EC0327](#) [HP471M250N300AP4](#) [TLS500V100M25.4*30 V](#) [KN331M40030*30A](#) [TLS315VS470M30*30 VS](#) [KM250M471SI225*35TA-1B3Et](#) [KS400M151SI222*30TA-1A1ET](#) [152EC0337](#)