



1. Features

KNX3403B is an N-channel enhancement mode power Mosfet field effect transistor which is produced using KIA's LVMosfet technology.the improved process and cell structure have been especially tailored to minimize on-state resistance,provide superior switching performance. This device is widely used in UPS,Power Management for Inverter Systems.

2. Features

- 85A, 30V, $R_{DS(on)}$ typ. = $4.5m\Omega$ (typ.)@ $V_{GS} = 10 V$
- Low gate charge
- Low Crss
- Fast switching
- Improved dv/dt capability

3. Pin configuration



Pin DFN5*6	Pin TO-252	Function
4	1	Gate
5,6,7,8	2	Drain
1,2,3	3	Source

4. Ordering Information

Part Number	Package	Brand
KND3403B	TO-252	KIA
KNY3403B	DFN5*6	KIA

5. Absolute maximum ratings

($T_C = 25^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Value	Units
V_{DSS}	Drain-Source Voltage	30	V
I_D	Drain Current -Continuous ($T_C = 25^\circ\text{C}$)	85	A
	-Continuous ($T_C = 100^\circ\text{C}$)	61	A
I_{DM}	Drain Current -Pulsed	340	A
V_{GSS}	Gate-Source Voltage	± 20	V
E_{AS}	Single Pulsed Avalanche Energy (Note 1)	156	mJ
P_D	Power Dissipation ($T_C = 25^\circ\text{C}$)	71	W
	-Derate above 25°C	0.47	W/ $^\circ\text{C}$
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to +150	$^\circ\text{C}$

6. Thermal Characteristics

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	2.1	$^\circ\text{C} / \text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	62	$^\circ\text{C} / \text{W}$

7. Electrical characteristics

($T_C = 25^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Off Characteristics						
$B_{V_{DS}}$	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$	30	--	--	V
I_{DSS}	Drain-Source Leakage Current	$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V}$	--	--	1	μA
I_{GSS}	Gate- Source Leakage Current	$V_{GS} = \pm 20\text{ V}, V_{DS} = 0\text{ V}$	--	--	± 100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	0.8	1.3	2.5	V
$R_{DS(on)}$	Static Drain-Source On-Resistance	$V_{GS} = 10\text{ V}, I_D = 20\text{ A}$	--	4.5	5.5	m Ω
		$V_{GS} = 4.5\text{ V}, I_D = 15\text{ A}$	--	5.5	7.2	m Ω
R_G	Gate Resistance	$f = 1.0\text{ MHz}$	--	5.0	--	Ω
Dynamic Characteristics						
C_{iss}	Input Capacitance	$V_{DS} = 25\text{ V}, V_{GS} = 0\text{ V},$ $f = 1.0\text{ MHz}$	--	2200	--	pF
C_{oss}	Output Capacitance		--	270	--	pF
C_{rss}	Reverse Transfer Capacitance		--	205	--	pF
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time	$V_{DD} = 20\text{ V}, V_{GS} = 4.5\text{ V},$ $I_D = 60\text{ A}, R_G = 1.8\text{ }\Omega$ (Note 2,3)	--	11	--	ns
t_r	Turn-On Rise Time		--	87	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	140	--	ns
t_f	Turn-Off Fall Time		--	82	--	ns
Q_g	Total Gate Charge	$V_{DD} = 24\text{ V}, I_D = 30\text{ A},$ $V_{GS} = 10\text{ V}$ (Note 2,3)	--	47	--	nC
Q_{gs}	Gate-Source Charge		--	8.5	--	nC
Q_{gd}	Gate-Drain Charge		--	9.9	--	nC
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Continuous Source Current	Integral Reverse P-N Junction Diode in the MOSFET	--	--	85	A
I_{SM}	Pulsed Source Current		--	--	340	A
V_{SD}	Drain-Source Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_S = 20\text{ A}$	--	--	1.4	V
t_{rr}	Reverse Recovery Time	$V_{GS} = 0\text{ V}, I_S = 30\text{ A},$ $dI_F / dt = 100\text{ A}/\mu\text{s}$ (Note 2)	--	15	--	ns
Q_{rr}	Reverse Recovery Charge		--	7.0	--	μC

Notes:

1. $L = 0.5\text{ mH}, V_{DD} = 15\text{ V}, V_{GS} = 10\text{ V}, R_G = 25\text{ }\Omega$, Starting $T_J = 25^\circ\text{C}$
2. Pulse Test : Pulse width $\leq 300\text{ }\mu\text{s}$, Duty cycle $\leq 2\%$
3. Essentially independent of operating temperature

8. Typical Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 5. Capacitance Characteristics








Figure 6. Gate Charge





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [KIA](#) manufacturer:

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [BUK455-60A/B](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#) [IPS70R2K0CEAKMA1](#) [SQD23N06-31L-GE3](#)
[TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [DMN1053UCP4-7](#) [SQJ469EP-T1-GE3](#) [NTE2384](#) [DMC2700UDMQ-7](#)
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [DMN2990UFB-7B](#)
[IPB80P04P405ATMA2](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [MCQ7328-TP](#) [BXP7N65D](#) [BXP4N65F](#) [AOL1454G](#) [WMJ80N60C4](#) [BXP2N20L](#)
[BXP2N65D](#) [BXT1150N10J](#) [BXT1700P06M](#) [TSM60NB380CP](#) [ROG](#) [RQ7L055BGTCR](#) [DMNH15H110SK3-13](#) [SLF10N65ABV2](#)
[BSO203SP](#) [BSO211P](#) [IPA60R230P6](#) [IPA60R460CE](#)