
THROUGH-HOLE LED LAMPS

Kingbright



	1 1						
Part No.	Emitting Color + Material	λD	Lens Type	lv (mcd) @2mA		Viewing Angle	Dimension
	+ Material	(n m)	-	Min.	Тур.	201/2	
L934LID	GaAsP/GaP	625	red diffused	0.8	3	60°	T-1 (3mm) Round 4.6(.181)±0.3 27(1.063)MIN
L934LGD	GaP	568	green diffused	0.8	2	60°	1(.04) 1.5(.06)TYP CATHODE
L934LYD	GaAsP/GaP	588	yellow diffused	0.8	2	60°	CATHODE (2) (3) (4) (7) (1.0 MAX) (
L934LSRD	GaAlAs	640	red diffused	8	20	60°	(1.0 MAX) 0.7 MAX. □ 0.5(0.02) (5.4(0.213) ±0.5
L53LID	GaAsP/GaP	625	red diffused	0.8	5	60°	T-1 3/4 (5mm) Round 8.6(.339) 27(1.063)MIN
L53LGD	GaP	568	green diffused	0.8	2	60°	5.9(.232) 1(.04) 1.5(.06)TYP
L53LYD	GaAsP/GaP	588	yellow diffused	0.8	2	60°	CATHODE CATHOLIC CATH
L53LSRD	GaAlAs	640	red diffused	8	20	60°	1.0 MAX. 0.7MAX. 0.5(0.02) ±0.05

Part No.	Emitting Color + Material	λD (nm)	Lens Type	lv (mcd) V=5V *V=12V, **V=14V		Viewing Angle	Dimension
				Min.	Тур.	201/2	
L934ID5V	GaAsP/GaP	625	red diffused	8	20	60°	T-1 (3mm) Round
L934ID12V	GaAsP/GaP	625	red diffused	*8	*20	60°	
L934ID14V	GaAsP/GaP	625	red diffused	**8	**20	60°	
L934GD5V	GaP	568	green diffused	8	20	60°	4 6(191)±0 3 07(4 067)4114
L934GD12V	GaP	568	green diffused	*8	*20	60°	4.6(.181)±0.3 27(1.063)MIN
L934GD14V	GaP	568	green diffused	**8	**25	60°	1(.04) 1.5(.06)TYP
L934YD5V	GaAsP/GaP	588	yellow diffused	8	15	60°	CATHODE
L934YD12V	GaAsP/GaP	588	yellow diffused	*8	*15	60°	
L934YD14V	GaAsP/GaP	588	yellow diffused	**3	**11	60°	2,000
L934SGD5V	GaP	568	green diffused	8	20	60°	
L934SGD12V	GaP	568	green diffused	*8	*20	60°	- 6
L934SGD14V	GaP	568	green diffused	**8	**25	60°	ο ο ο [5.4(0.213)]
L934SRD5V	GaAlAs	640	red diffused	70	150	60°	2 2 ±0.5
L934SRD12V	GaAlAs	640	red diffused	*40	*100	60°	
L934SRD14V	GaAlAs	640	red diffused	**28	**90	60°	

L53ID5V	GaAsP/GaP	625	red diffused	12	30	60°	T-1 3/4 (5mm) Round
L53ID12V	GaAsP/GaP	625	red diffused	*12	*30	60°	
L53ID14V	GaAsP/GaP	625	red diffused	**18	**65	60°	
L53GD5V	GaP	568	green diffused	8	20	60°	8.6(.339) 27(1.063)MIN
L53GD12V	GaP	568	green diffused	*8	*20	60°	
L53GD14V	GaP	568	green diffused	**5	**18	60°	5.9(.232) 1(.04) 1.5(.06)TYP
L53YD5V	GaAsP/GaP	588	yellow diffused	5	20	60°	
L53YD12V	GaAsP/GaP	588	yellow diffused	*5	*20	60°	CATHODE
L53YD14V	GaAsP/GaP	588	yellow diffused	**5	**16	60°	
L53SGD5V	GaP	568	green diffused	8	20	60°	
L53SGD12V	GaP	568	green diffused	*8	*20	60°	
L53SGD14V	GaP	568	green diffused	**5	**18	60°	1.0 MAX. 0.7MAX. 0.5(0.02) ±0.05
L53SRD5V	GaAlAs	640	red diffused	100	180	60°	
L53SRD12V	GaAlAs	640	red diffused	*100	*180	60°	
L53SRD14V	GaAlAs	640	red diffused	**70	**160	60°	

NOTES:

- 1. All dimensions are in millimeters (inches)
 2. Tolerance is ±0.25mm(0.01") unless otherwise noted.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard LEDs - Through Hole category:

Click to view products by Kingbright manufacturer:

Other Similar products are found below:

LTL-10254W LTL-1214A LTL-2231AT LTL-3251A LTL-4262N LTL-433P LTL-5234 LTL87HTBK LTW-87HD4B HLMP-EL30-PS0DD 1L0532V23G0TD001 NSPW500CS NTE30036 NTE30044 NTE30059 NTE3020 LD CQDP-1U3U-W5-1-K

LP379PPG1C0G0300001 SLR-342MC3F SLX-LX3044GD SLX-LX3044ID SLX-LX3044YD 1.90690.3330000 SSS-LX4673ID-410B

1L0532Y24I0TD001 264-7SYGD/S530-E2 HLMP-1301-G00FG HLMP1385 LTL-10224W LTL-1224A LTL-1234A LTL-2251AT LTL-403HR LTL-4222 LU7-E-B 4380H1 HLMP-3962-F0002 HLMP-GG15-R0000 323-2SURD/S530-A3 L53SRC/E-Z L-7679C1ZGC

4302T1-5V 4306D23 4363D1/5 WP1503SRC/J4 WP153GDT WP153YDT WP1543SGC WP1543SURC WP53MGD