



### SPECIFICATIONS

Current Rating: 3Amps  
 Insulation Resistance: 1000MΩ Min  
 Contact Resistance: 20mΩ Max  
 Withstanding Voltage: AC 1000V  
 Operation Temperature: -40° to +105°  
 Contact Material: Brass  
 Standard: PA6T  
 Insulator Material: Polyester (UL 94V-0)  
 Contact Plating: Gold Flash  
 Max. Processing Temp: 240° C for 30-60 seconds  
 (260° C for 5 seconds)

深圳市金航标电子有限公司 KH-2.54PH-1X28P-L13.5-WT		www.kinghelm.com.cn 0755-28190160		No. of 1 2 3 4 5 6 7 8 9 10		DIM. A 0.00 2.54 5.08 7.62 10.16 12.70 15.24 17.78 20.32 22.86		DIM. B 2.54 5.08 7.62 10.16 12.70 15.24 17.78 20.32 22.86 25.40		No. of 11 12 13 14 15 16 17 18 19 20		DIM. A 25.40 27.94 30.48 33.02 35.56 38.10 40.64 43.18 45.72 48.26		DIM. B 27.94 30.48 33.02 35.56 38.10 40.64 43.18 45.72 48.26 50.80		No. of 21 22 23 24 25 26 27 28 29 30		DIM. A 50.80 53.34 55.88 58.42 60.96 63.50 66.04 68.58 71.12 73.66		DIM. B 53.34 55.88 58.42 60.96 63.50 66.04 68.58 71.12 73.66 76.20		No. of 31 32 33 34 35 36 37 38 39 40		DIM. A 76.20 78.74 81.28 83.82 86.36 88.90 91.44 93.98 96.52 99.06		DIM. B 78.74 81.28 83.82 86.36 88.90 91.44 93.98 96.52 99.06 101.60	
UNLESS OTHERWISE SPECIFIED TOLERANCE X : ±0.30 X° : ±5° X.X : ±0.25 X.X° : ±1° X.XX : ±0.20 X.XX° : ±0.5°				DRAWING NAME: 2.54PH H2.5 1x28Pin 卧贴 PC4.8 PA6.0 L13.5 6T 贴板长度2.3				SIZE A4 SCALE N:1 PROUCT NO.		REV B UNIT mm PROJECT		PAGE 1/1		CHECKED: 陈超凡 2022/05/19		CHECKED: / /		APPROVED: / /									

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Kinghelm](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)