



SPECIFICATIONS

Current Rating: 3Amps
 Insulation Resistance: 1000MΩ Min
 Contact Resistance: 20mΩ Max
 Withstanding Voltage: AC 1000V
 Operation Temperature: -40 ° to+105°
 Contact Material: Brass
 Standard: PBT
 Insulator Material: Polyester(UL 94V-0)
 Contact Plating: Gold Flash
 Max.Processing Temp: 200 ° C for30-60seconds
 (220 ° C for5seconds)

- (1) Pin Spacing: 254=2.54mm
- (2) Product Name: PH=Pin Header
- (3) No. of Rows: 1=Single Row ; 2=Dual Row
- (4) No. of Pins Per Row: 1~40
- (5) Insulator Material Height: 15=1.5mm; 20=2.0mm; 25=2.5mm
- (6) Connector Type: S=Straight; R=Right; Angle M=SMT
- (7) Contact Material Length: 116=11.6mm 130=13.0mm
- (8) No. of Insulator Material: 1=1PCS; 2=2PCS; 3=3PCS
- (9) Contact Plating:
 SN=Tin; G0=Gold Flash; S0=Gold Flash/Tin; AU08=Au 0.8u"
- (10) Insulator Material Option:
 A=BK-PBT; B=BK-PA6T; C=BK-PA46; D=KB-LCP; S=Special

深圳市金航标电子有限公司				WWW.BDS666.COM				No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B		
KH-2.54PH90-1X15P-L13.8				0755-83044319				1	0.00	2.54	11	25.40	27.94	21	50.80	53.34	31	76.20	78.74		
<small>UNLESS OTHERWISE SPECIFIED TOLERANCE</small> X : ±0.3 X° : ±5° X.X : ±0.2 X.X° : ±1° X.XX : ±0.1 X.XX° : ±0.5°				<small>DRAWM NAME:</small> 2.54PH 1xnPin H2.5 90° L13.8 反弯				2	2.54	5.08	12	27.94	30.48	22	53.34	55.88	32	78.74	81.28		
SIZE	A4	SCALE	N: 1	PROJECT NO.		3	5.08	7.62	13	30.48	33.02	23	55.88	58.42	33	81.28	83.82				
REV	A	UNIT	mm	PROJECT		4	7.62	10.16	14	33.02	35.56	24	58.42	60.96	34	83.82	86.36				
<small>CHECKED: LI BEI LIN 12/03/07</small>				<small>CHECKED: / /</small>				<small>APPROVED: / /</small>		5	10.16	12.70	15	35.56	38.10	25	60.96	63.50	35	86.36	88.90
<small>CHECKED: / /</small>				<small>APPROVED: / /</small>				6	12.70	15.24	16	38.10	40.64	26	63.50	66.04	36	88.90	91.44		
<small>CHECKED: / /</small>				<small>APPROVED: / /</small>				7	15.24	17.78	17	40.64	43.18	27	66.04	68.58	37	91.44	93.98		
<small>CHECKED: / /</small>				<small>APPROVED: / /</small>				8	17.78	20.32	18	43.18	45.72	28	68.58	71.12	38	93.98	96.52		
<small>CHECKED: / /</small>				<small>APPROVED: / /</small>				9	20.32	22.86	19	45.72	48.26	29	71.12	73.66	39	96.52	99.06		
<small>CHECKED: / /</small>				<small>APPROVED: / /</small>				10	22.86	25.40	20	48.26	50.80	30	73.66	76.20	40	99.06	101.60		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Kinghelm](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)