



- (1) Pin Spacing: 254=2.54mm
- (2) Product Name: PH=Pin Header
- (3) No. of Rows: 1=Single Row ; 2=Dual Row
- (4) No. of Pins Per Row: 1~40
- (5) Insulator Material Height: 15=1.5mm; 20=2.0mm; 25=2.5mm
- (6) Connector Type: S=Straight; R=Right; Angle M=SMT
- (7) Contact Material Length: 116=11.6mm 130=13.0mm
- (8) No. of Insulator Material: 1=1PCS; 2=2PCS; 3=3PCS
- (9) Contact Plating:  
SN=Tin; G0=Gold Flash; S0=Gold Flash/Tin; AU08=Au 0.8u"
- (10) Insulator Material Option:  
A=BK-PBT; B=BK-PA6T; C=BK-PA46; D=KB-LCP; S=Special

|  |  |   |       |        |        |        |        |        |        |        |        |        |        |        |        |       |      |       |       |       |       |       |       |       |        |
|--|--|---|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|------|-------|-------|-------|-------|-------|-------|-------|--------|
| 深圳市金航标电子有限公司<br>WWW.BDS666.COM   |  | KH-2.54PH90-1X20P-L13.8<br>0755-83044319      |       | No. of | DIM. A | DIM. B | No. of | DIM. A | DIM. B | No. of | DIM. A | DIM. B | No. of | DIM. A | DIM. B |       |      |       |       |       |       |       |       |       |        |
|  |  |   |       | 1      | 0.00   | 2.54   | 11     | 25.40  | 27.94  | 21     | 50.80  | 53.34  | 31     | 76.20  | 78.74  | 2     | 2.54 | 5.08  | 12    | 27.94 | 30.48 | 22    | 53.34 | 55.88 | 32     |
| UNLESS OTHERWISE SPECIFIED TOLERANCE<br>X : $\pm 0.3$ X° : $\pm 5^\circ$<br>X.X : $\pm 0.2$ X.X° : $\pm 1^\circ$<br>X.XX : $\pm 0.1$ X.XX° : $\pm 0.5^\circ$ |  | DRAWING NAME: 2.54PH 1xnPin H2.5 90° L13.8 反弯 |       |        |        |        |        |        |        |        |        |        |        |        |        |       |      |       |       |       |       |       |       |       |        |
|  |  | 3   | 5.08  | 7.62   | 13     | 30.48  | 33.02  | 23     | 55.88  | 58.42  | 33     | 81.28  | 83.82  | 4      | 7.62   | 10.16 | 14   | 33.02 | 35.56 | 24    | 58.42 | 60.96 | 34    | 83.82 | 86.36  |
| CHECKED: LI BEI LIN 12/03/07<br>CHECKED: / /<br>APPROVED: / /  |  | 5   | 10.16 | 12.70  | 15     | 35.56  | 38.10  | 25     | 60.96  | 63.50  | 35     | 86.36  | 88.90  | 6      | 12.70  | 15.24 | 16   | 38.10 | 40.64 | 26    | 63.50 | 66.04 | 36    | 88.90 | 91.44  |
|  |  | 7   | 15.24 | 17.78  | 17     | 40.64  | 43.18  | 27     | 66.04  | 68.58  | 37     | 91.44  | 93.98  | 8      | 17.78  | 20.32 | 18   | 43.18 | 45.72 | 28    | 68.58 | 71.12 | 38    | 93.98 | 96.52  |
| SIZE A4 SCALE N:1 PROJECT NO. PROJECT  PAGE 1/1  |  | 9   | 20.32 | 22.86  | 19     | 45.72  | 48.26  | 29     | 71.12  | 73.66  | 39     | 96.52  | 99.06  | 10     | 22.86  | 25.40 | 20   | 48.26 | 50.80 | 30    | 73.66 | 76.20 | 40    | 99.06 | 101.60 |
|  |  | 1   | 2     | 3      | 4      | 5      | 6      | 7      | 8      | 9      |        |        |        |        |        |       |      |       |       |       |       |       |       |       |        |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Kinghelm](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)