



1. Material:
Contacteis: Phosphore
Bronze
insulater: PBT+30%
G. F. UL 94V-0
Shell: SPCC
2. Mechanical:
Mating: .35N max.
Withdrowa Force: 10N min.
Darability: 1500 cycles min.
3. Elecetical:
Current-max (amps) 1.5A
Voitage-max (volts) 30V
Withstanding Voltage 750V AC
Contact Resistance (ohms) 30
milliohms max insulation
Resistance (ohms) 1000 Megogms
min.
4. Plating:
Contacts: Gold And Tin Over
Nickel Ploled
Shell: Nickel over all plating.
5. Environmental:
temperatue Range: -55 to 85 .

产品图

MANUFACTURE Dwg

公差一览表

TOLERANCE UNLESS OTHERWISE

单位 UNIT	MM	INCH
X	±0.20	±
XX	±0.10	±
.XXX	±0.05	±

2013. 08. 29

深圳市金航标电子有限公司		WWW.BDS666.COM	
KH-2AF180YC-10.5JB		0755-83044319	
产品名称		制图	审核
角法 VIEW	比例 1:1	DRAWING 设计	CHEK 核准
SCALE	版本 AI	图号	CXCI

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Kinghelm](#) manufacturer:

Other Similar products are found below :

[950](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#)
[1734082-1](#) [30-470](#) [30-489](#) [30-541](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTVSCCG](#) [1-1734084-2](#) [10135326-001LF](#) [4198](#) [USB-A-D-VT](#)
[USB-A-S-RA-TSMT](#) [1310-1023-02](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [17-200011](#) [UB-20AFMM-LL7A01](#) [1040870124](#) [CAP-](#)
[WCCMLPB1](#) [CAP-WCCMLPC1](#) [2274475-3](#) [UB-20BMFA-SL8001](#) [914-614A2025S10200](#) [USB3FTV7SAGF059](#) [ZX40-B-5S-1500-](#)
[STDA\(30\)](#) [GSB3116344HR](#) [USB3FTV2SAZNF459](#) [USB3FTV7SAZNF459](#) [U221-041N-1WVS62-F5D](#) [HYCW153-USBD05-500B](#)
[HYCW219-USBD05-075B](#) [HYCW148-USBD05-117B](#) [HYCW149-USBD05-740B](#) [HYCW204-USBD05-108B](#) [HYCW214-USBA04-113B](#)
[HYCW213-USBA04-113B](#) [UB-20AMFM-SL7A01](#) [KMMX-BSMT35S-1-B30TR](#) [2345986-1](#)