



2~5A

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated

编号	尺寸 (mm)	
	A	B
A2508-02A	2.50	7.50
A2508-03A	5.00	10.00
A2508-04A	7.50	12.50
A2508-05A	10.00	15.00
A2508-06A	12.50	17.50
A2508-07A	15.00	20.00
A2508-08A	17.50	22.50
A2508-09A	20.00	25.00
A2508-10A	22.50	27.50
A2508-11A	25.00	30.00
A2508-12A	27.50	32.50
A2508-13A	30.00	35.00
A2508-14A	32.50	37.50
A2508-15A	35.00	40.00
A2508-20A	47.50	52.50

PCB LAYOUT

GENERAL TOLERANCE		制图	钱岳生		料号	A2508-nA		版本	A
X.±0.25	X.*±2'	DRAWING	2013、07、01		PART NO.	XA单排直针		REV.	1/1
.X±0.20	.X*±1'	审核	张名		TITLE	WAFER DIP TYPE		SHEET	1/1
.XX±0.15	.XX*±0.5'	CHECK	2013、07、03		CUTM. NO.				
.XXX±0.10	.XXX*±0.5'	核准	张名		深圳市金航标电子有限公司		www.kinghel.m.com.cn		
UNITS	MM	比例	1:1		KH-A2508-04A		0755-28190160		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Kinghelm](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [M90C108951C](#)
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-024-10-](#)
[001000](#) [803-93-012-10-001000](#)