		B	C		D	
4	 MATERIAL: 2.1. SEE TABLE ALL COMPONENTS ARE ROHS COMPLIANT. 	54321 Π				4
CUSTOMER PN:	NT.	ES: VOLTAGE RATING:DCV 300V 10MS CONDUCTANCE RESISTANCE: 3.0 OHM/MAX. INSULATION RESISTANCE: 5.0M OHM/MIN. THE CABLE SHOULD BE 100% ELECTRICAL TEST IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES.	L1 50±1 L2 60±1 L3 120±1		150	ω
CHKD. Frank 2 Computer Generation PROJECTION APPD. Sout 2 PROJECTION GENERAL TOLERANCE FOR ANGLES XX XXX XXXX ±1° ±0.3 ±0.25 ±	深圳市会航 ALL DIMENSION DRAWN James DATE	ITEM PART NUMBER NO. PART NUMBER ② 端子 ① 同轴线			150mm±5mm	2 REV NUMBER DESIGN DESIGN
019-06-01		DESCRIPITION QTY. 高仿I-PEX 1.13端子,镀金 1 RF1.13灰色同釉线,OD:1.13mm As				REVISIONS DESCRIPTION DWN CHK DATE
		,		0	C	 ⊃

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Kinghelm manufacturer:

Other Similar products are found below :

 CCT
 FM1
 ABFT
 AD-NM-SMAF
 001-0021
 CTC110
 MAF94149
 EXE902SF
 MMCX-SMA-100
 PDQ24496-91NF
 GAN30084EU
 930

 033-R
 A08-HABUF-P5I
 AAF95035
 DG-ANT-20DP-BG-B
 APAMPGJ-141
 1513563-1
 OF86315-FNF
 OP24516DS-91NM
 A09-HASM-7

 EXE902MD
 EXE902SM
 SPDA17806/2170LAR
 APAMPG-117
 GPS1575SP26-004
 GPS15MGSMA
 CMD69273P-30NF
 CMQ69273-30NF

 RD2458-5-OTDR-NM
 RD2458-5-RSMA
 TRAB24/49003
 W4120ER5000
 W6102B0100
 YE572113-30RSMM
 108-00014-50

 SPDA17RP918
 OP24516SX-91NM
 OP24516SX-91RSMM
 CMQ69273P-30NF
 CMS69273-30NF
 CMS69273P-30NF
 TRAB24003N

 TRAB24003NP
 TRAB8903
 A09-Y8NF
 A09-Y11NF
 A09-F8NF-M
 A09-F5NF-M