	Þ	œ	C	D
4		 ELECTRICAL: VOLTAGE RATING:DCV 300V 10MS CONDUCTANCE RESISTANCE: 3.0 OHM/MAX. INSULATION RESISTANCE: 5.0M OHM/MIN. THE CABLE SHOULD BE 100% ELECTRICAL TEST IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES MATERIAL: MATERIAL: SEE TABLE MECHANICALL: SMA PULL FORCE: 12.0KGS. ALL COMPONENTS ARE RoHS COMPLIANT. 	NOTES:	4
ω		AAX. AL TEST SWIRING AND INTERMITTENT FAILURES	15+/-1 1個配作出館時另外附配作出 貸(2个华司,1个爆略)	3
-	ALL DIMENSION ARE IN MM COMPUTER GENERATED IN SOLDWORKS DO NOT SCALE THIS DRAWING PROJECTION PROJECTION GENERAL ANGLES ± 1°	NO. PART NUMBER NO. PART NUMBER		100mm ± 5
2		黑色热缩套管, 高仿I-PEX,1.13 SMA母头内孔,分 RF 1.13灰色线,C 九 标 电		2 <u>A</u> <u>NUMBER</u> <u>DESIGN</u> <u>F</u> KHB(RG113)-100-29
	O SMA /F L	DESCRIPTION OD:2.0MM 端子, 镀金 ^体, 11牙, 镀金 DD:1.13mm 子 有 限		EVISIONS
		Image: bit with the second	_	DWN CHK DATE
	\triangleright		C	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Kinghelm manufacturer:

Other Similar products are found below :

 CCT
 FM1
 ABFT
 AD-NM-SMAF
 001-0021
 CTC110
 MAF94149
 EXE902SF
 MMCX-SMA-100
 PDQ24496-91NF
 GAN30084EU
 930

 033-R
 A08-HABUF-P5I
 AAF95035
 DG-ANT-20DP-BG-B
 APAMPGJ-141
 1513563-1
 OF86315-FNF
 OP24516DS-91NM
 A09-HASM-7

 EXE902MD
 EXE902SM
 SPDA17806/2170LAR
 APAMPG-117
 GPS1575SP26-004
 GPS15MGSMA
 CMD69273P-30NF
 CMQ69273-30NF

 RD2458-5-OTDR-NM
 RD2458-5-RSMA
 TRAB24/49003
 W4120ER5000
 W6102B0100
 YE572113-30RSMM
 108-00014-50

 SPDA17RP918
 OP24516SX-91NM
 OP24516SX-91RSMM
 CMQ69273P-30NF
 CMS69273-30NF
 CMS69273P-30NF
 TRAB24003N

 TRAB24003NP
 TRAB8903
 A09-Y8NF
 A09-Y11NF
 A09-F8NF-M
 A09-F5NF-M