	Þ	œ	O	D
4		<ol> <li>1.1. VOLTAGE RATING:DCV 300V 10MS</li> <li>1.2. CONDUCTANCE RESISTANCE: 3.0 OHM/MAX.</li> <li>1.3. INSULATION RESISTANCE: 5.0M OHM/MIN.</li> <li>1.4. THE CABLE SHOULD BE 100% ELECTRICAL TEST</li> <li>1.5. IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING</li> <li>2. MATERIAL:</li> <li>2.1. SEE TABLE</li> <li>3. MECHANICALL:</li> <li>3.1. SMA PULL FORCE: 12.0KGS.</li> <li>4. ALL COMPONENTS ARE RoHS COMPLIANT.</li> </ol>	NOTES: 1. ELECTRICAL:	
ω	CUSTOMER P/N:	MAX. IN. DAL TEST ISWIRING AND INTERMITTENT FAILURES	15+/-1 三個配件出貨時另外附配件出 貨(2个华司,1个螺母)	<u>υ</u>
	ALL DIMENSION ARE IN MM COMPUTER GENERATED IN SOLIDWORKS DO NOT SCALE THIS DRAWING PROJECTION PROJECTION ANGL 41	· · · · · · · · · · · · · · · · · · ·	TTEM PART NUMBER	55mm —
2	RAWN     Jamy     DATE     2018/05/04       VG.	黑色热缩套管, 高仿I-PEX,1.13 SMA母头内孔,分 RF 1.13 黑色线,C 九		2 REV NUMBER REVISI A DESIGN BESIGN KHB(RG113)-55-29
	TITLE RF CABLE I-PEX 1.13 TO SMA /F L=55 MM SIZE Number B SCALE: Free TYPE SHEET 1 C	2.0MM 2.0MM 11牙、镀金 11牙、镀金 .13mm 子 有 际		REVISIONS 1 DESCRIPTION DWN
	SHEET 1 OF 1		OTY C	

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Kinghelm manufacturer:

Other Similar products are found below :

 CCT
 FM1
 ABFT
 AD-NM-SMAF
 001-0021
 CTC110
 MAF94149
 EXE902SF
 MMCX-SMA-100
 PDQ24496-91NF
 GAN30084EU
 930 

 033-R
 A08-HABUF-P5I
 AAF95035
 DG-ANT-20DP-BG-B
 APAMPGJ-141
 1513563-1
 OF86315-FNF
 OP24516DS-91NM
 A09-HASM-7

 EXE902MD
 EXE902SM
 SPDA17806/2170LAR
 APAMPG-117
 GPS1575SP26-004
 GPS15MGSMA
 CMD69273P-30NF
 CMQ69273-30NF

 RD2458-5-OTDR-NM
 RD2458-5-RSMA
 TRAB24/49003
 W4120ER5000
 W6102B0100
 YE572113-30RSMM
 108-00014-50

 SPDA17RP918
 OP24516SX-91NM
 OP24516SX-91RSMM
 CMQ69273P-30NF
 CMS69273-30NF
 CMS69273P-30NF
 TRAB24003N

 TRAB24003NP
 TRAB8903
 A09-Y8NF
 A09-Y11NF
 A09-F8NF-M
 A09-F5NF-M