



**NOTES:**

- \*Material
  - Body: LCP Rated: Color: Black.
  - Shield: Brass
  - plating: Nickel Plating.
  - Contact: Phosphor Bronze.
  - plating: Gold plating Over Nickel on contact Area; Tin plating on solder tail
- \*Electrical Specification
  - Operation Voltage: 40 VAC max
  - Current Rating: 0.5 Ampere per contact
  - Contact Resistance: 30 Milliohms max.
  - Insulation Resistance: 2000 Megohms min.
  - Dielectric Withstanding Voltage: 500VAC
- \*Environmental
  - Operating Temperature: -20C to +85C
- \*How TO Order

深圳市金航标电子有限公司	www.kinghelm.com.cn	HD-0013								P/No:	
		Customer:	Approval	Check	Drawn	Unit	Scale			Date	Pin Longer
KH-HDMI-0013	0755-28190160	Drawing No:			babm	mm			Signal Level		

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub Standard Connectors](#) category:*

*Click to view products by [Kinghelm](#) manufacturer:*

Other Similar products are found below :

[015-0339-000](#) [015-0341-000](#) [015-0349-000](#) [015-0350-000](#) [015-8544-011](#) [015-8755-001](#) [017041-0005](#) [020419-0104](#) [609-25P](#) [609-9P](#)  
[M24308/2-23Z](#) [CT0-24-10SC](#) [CT0-36-3PC](#) [CT0E20-8PS](#) [CT0F16S-1PS](#) [CT0TA16-11SXCA232](#) [CT1E20-19SS](#) [CT2-10SL-3SC](#) [CT2-14S-2PCA34](#) [CT2-18-11PCAU](#) [CT2-22-19SC](#) [CT2-36-5PC](#) [CT6-10SL-3SC](#) [CT6-10SL-4SC](#) [CT6-14S-2SC](#) [CT6-16-12SC](#) [CT6-18-10PSA206](#)  
[CT6-18-10PSA232](#) [CT6-18-11PXSA206](#) [CT6-18-11PXSA232](#) [CT6-22-10PS](#) [CT6-24-5PC](#) [CT6-9767-18-8-18-4SS](#) [CT6E14S-5SC](#)  
[CT6E14SA7SC](#) [CT6E20-14SS](#) [CT6E22-14PC](#) [CT6E22-14PS](#) [CT6E22-19PS](#) [CT6E22-22PS](#) [CT6E24-10SC](#) [CT6F16S-1SC](#) [CT6FA10SL-4PS](#)  
[CT6LA20-19PC](#) [CT6M20-19SS](#) [CT6NSB4-20-8SS](#) [CT6TC14S-6SCAU](#) [CT6TC14S-7PS](#) [6STD15SCT99S40X](#) [6STF09PCM05B70X](#)