

## KVR16LR11D4/16HA

16GB 2Rx4 2G x 72-Bit PC3L-12800  
CL11 Registered w/Parity 240-Pin DIMM

### DESCRIPTION

This document describes ValueRAM's 2G x 72-bit (16GB) DDR3L-1600 CL11 SDRAM (Synchronous DRAM), registered w/parity, low voltage, 2Rx4 ECC, memory module, based on thirty-six 1G x 4-bit FBGA components. The SPD is programmed to JEDEC standard latency DDR3-1600 timing of 11-11-11 at 1.35V and 1.5V. This 240-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

### FEATURES

- JEDEC standard 1.35V (1.28V ~ 1.45V) and 1.5V (1.425V ~ 1.575V) Power Supply
- VDDQ = 1.35V (1.28V ~ 1.45V) and 1.5V (1.425V ~ 1.575V)
- 800MHz fCK for 1600Mb/sec/pin
- 8 independent internal bank
- Programmable CAS Latency: 11, 10, 9, 8, 7, 6
- Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- 8-bit pre-fetch
- Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- Bi-directional Differential Data Strobe
- Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm ± 1%)
- On Die Termination using ODT pin
- On-DIMM thermal sensor (Grade B)
- Average Refresh Period 7.8us at lower than TCASE 85°C, 3.9us at 85°C < TCASE ≤ 95°C
- Asynchronous Reset
- PCB : Height 1.180" (30.00mm), double sided component

### SPECIFICATIONS

|  |  |
|--|--|
| CL(IDD)  | 11 cycles                                |
| Row Cycle Time (tRCmin)                          | 48.125ns (min.)                          |
| Refresh to Active/Refresh Command Time (tRFCmin) | 260ns (min.)                             |
| Row Active Time (tRASmin)                        | 35ns (min.)                              |
| Maximum Operating Power                          | (1.35V) = 4.943 W*<br>(1.50V) = 6.033 W* |
| UL Rating  | 94 V - 0                                 |
| Operating Temperature                            | 0° C to 85° C                            |
| Storage Temperature                              | -55° C to +100° C                        |


\*Power will vary depending on the SDRAM and Register/PLL used.

### SDRAM SUPPORTED


|             |
|-------------|
| Hynix A-Die |
|-------------|

Continued >>

### MODULE DIMENSIONS:



(Units = millimeters)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [kingston manufacturer](#):*

Other Similar products are found below :

[SDCA3/32GB](#) [SM2280S3G2/120G](#) [04EPOP08-NL3DM627-B02U](#) [SD4/32GB](#) [SEDC400S37/960G](#) [EMMC16G-W525-X01U](#) [08EPOP04-NL3DT227-A01U](#) [SEDC1000H/1600G](#) [04EMCP04-NL2DM627-Z02U](#) [08EMCP04-NL3DT227-A01U](#) [B1621PM1WDGTKR-U](#)  
[B5116ECMDXGGB-U](#) [EMMC04G-W100-E08U](#) [SDA10/128GB](#) [KVR13N9S8H/4](#) [D5128EETBPGGBU-U](#) [SDA3/32GB](#)  
[D5128EC4BPGGBUI-U](#) [SKC400S37/1T](#) [KVR21R15D4/16](#) [CF/256](#) [SUV400S37/240G](#) [SKC400S37/512G](#) [EMMC04G-M627-A01](#)  
[BOXSIZE 4](#) [BOXSIZE 3](#)