

## KVR18R13D4K4/64

64GB (16GB 2Rx4 2G x 72-Bit x 4 pcs.) PC3-14900  
CL13 Registered w/Parity 240-Pin DIMM Kit

### DESCRIPTION

ValueRAM's KVR18R13D4K4/64 is a kit of four 2G x 72-bit (16GB) DDR3-1866 CL13 SDRAM (Synchronous DRAM), registered w/parity, 2Rx4 ECC memory modules, based on thirty-six 1G x 4-bit FBGA components per module. Total kit capacity is 64GB. The SPDs are programmed to JEDEC standard latency DDR3-1866 timing of 13-13-13 at 1.5V. Each 240-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

### FEATURES

- JEDEC standard 1.5V (1.425V ~1.575V) Power Supply
- VDDQ = 1.5V (1.425V ~ 1.575V)
- 933MHz fCK for 1866Mb/sec/pin
- 8 independent internal bank
- Programmable CAS Latency: 13, 11, 10, 9, 8, 7, 6
- Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- 8-bit pre-fetch
- Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- Bi-directional Differential Data Strobe
- Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm  $\pm$  1%)
- On Die Termination using ODT pin
- On-DIMM thermal sensor (Grade B)
- Average Refresh Period 7.8us at lower than TCASE 85°C, 3.9us at 85°C < TCASE  $\leq$  95°C
- Asynchronous Reset
- PCB : Height 1.180" (30.00mm), double sided component


### SPECIFICATIONS

|  |                       |
|--|-----------------------|
| CL(IDD)  | 13 cycles             |
| Row Cycle Time (tRCmin)                          | 47.125ns (min.)       |
| Refresh to Active/Refresh Command Time (tRFCmin) | 260ns (min.)          |
| Row Active Time (tRASmin)                        | 34ns (min.)           |
| Maximum Operating Power                          | 6.330 W* (per module) |
| UL Rating  | 94 V - 0              |
| Operating Temperature                            | 0° C to 85° C         |
| Storage Temperature                              | -55° C to +100° C     |


\*Power will vary depending on the SDRAM and Register/PLL used.

Continued >>


### MODULE DIMENSIONS



### Back



### Side




**Note:**

1. ±0.13 tolerance on all dimensions unless otherwise stated.

**Units: millimeters**

# HEAT SPREADER



- Note:**
- 1. ±0.13 tolerance on all dimensions unless otherwise stated.
  - 2. In order to uninstall FDHS, please contact sales administrator.

**Units: millimeters**

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [kingston manufacturer](#):*

Other Similar products are found below :

[SDCA3/32GB](#) [SM2280S3G2/120G](#) [04EPOP08-NL3DM627-B02U](#) [SD4/32GB](#) [SEDC400S37/960G](#) [EMMC16G-W525-X01U](#) [08EPOP04-NL3DT227-A01U](#) [SEDC1000H/1600G](#) [04EMCP04-NL2DM627-Z02U](#) [08EMCP04-NL3DT227-A01U](#) [B1621PM1WDGTKR-U](#)  
[B5116ECMDXGGB-U](#) [EMMC04G-W100-E08U](#) [SDA10/128GB](#) [KVR13N9S8H/4](#) [D5128EETBPGGBU-U](#) [SDA3/32GB](#)  
[D5128EC4BPGGBUI-U](#) [SKC400S37/1T](#) [KVR21R15D4/16](#) [CF/256](#) [SUV400S37/240G](#) [SKC400S37/512G](#)