


Slogging Wrench



Please wear proper safety gear while working.

10A0


- Open end slogging
- Finished with phosphate sunk
- DIN 133



KT NO.	Size mm	L mm	D mm	H mm		
10A0-24	24	178	52	15	286	6 / 72
10A0-27	27	180	55	16	339	6 / 72
10A0-30	30	190	60	16	416	6 / 60
10A0-32	32	190	61	17	401	6 / 60
10A0-36	36	215	72	17	573	6 / 24
10A0-41	41	233	83	19	855	5 / 20
10A0-46	46	255	94	20	1102	4 / 16
10A0-50	50	275	105	22	1502	2 / 16
10A0-55	55	298	115	24	2161	2 / 12
10A0-60	60	320	127	24	2374	1 / 10
10A0-65	65	340	138	27	3204	1 / 8
10A0-70	70	370	156	32	3785	1 / 5
10A0-75	75	372	153	31	3715	1 / 5
10A0-80	80	395	175	33	6820	1 / 4
10A0-85	85	395	175	33	6300	1 / 4
10A0-90	90	440	197	38	9270	1 / 2
10A0-95	95	440	197	38	8700	1 / 2
10A0-A0	100	480	230	45	10500	1 / 2
10A0-A5	105	480	230	45	10300	1 / 2
10A0-B0	110	505	238	47	14420	1 / 1
10A0-B5	115	505	250	53	14420	1 / 1
10A0-C0	120	530	258	53	15450	1 / 1
10A0-C5	125	530	258	56	15015	1 / 1

10B0

- Ring slogging
- Finished with phosphate sunk
- DIN 7444



KT NO.	Size mm	L mm	D mm	H mm		
10B0-24	24	162	42	16	238	6 / 72
10B0-26	26	180	46	17	341	6 / 72
10B0-27	27	180	46	17	330	6 / 72
10B0-30	30	190	52	18	431	6 / 72
10B0-32	32	190	52	18	404	6 / 60
10B0-36	36	205	58	19	534	6 / 36
10B0-41	41	230	66	21	728	6 / 24
10B0-46	46	240	74	23	877	4 / 16
10B0-50	50	250	82	23	1085	4 / 16
10B0-55	55	265	88	24	1429	2 / 16
10B0-60	60	275	95	26	1644	2 / 12
10B0-65	65	295	104	28	1875	2 / 12
10B0-70	70	325	112	33	2965	1 / 8
10B0-75	75	325	115	33	2735	1 / 8
10B0-80	80	345	128	36	3675	1 / 6
10B0-85	85	345	130	36	3710	1 / 6
10B0-90	90	380	152	40	5850	1 / 4
10B0-95	95	380	152	40	5350	1 / 4
10B0-A0	100	410	161	43	6445	1 / 4
10B0-A5	105	415	172	45	6500	1 / 3
10B0-B0	110	440	172	47	8000	1 / 3
10B0-B5	115	440	172	47	7500	1 / 3
10B0-C0	120	470	194	53	9000	1 / 2

Heavy Duty Offset Ring Wrench

10C0

- To be used with extension tubes item "11"
- Chrome vanadium alloy steel
- Chrome plated



KT NO.	Size mm	L mm	Applied tube		
10C0-24	24	178	111946	463	6 / 48
10C0-27	27	188	111946	523	6 / 48
10C0-30	30	198	111946	579	4 / 36
10C0-32	32	233	112261	841	4 / 24
10C0-36	36	241	112261	946	4 / 24
10C0-41	41	260	112261	1099	2 / 16
10C0-46	46	277	112576	1365	2 / 16
10C0-50	50	287	112576	1642	2 / 16
10C0-55	55	298	112576	1766	1 / 12
10C0-60	60	345	113086	2800	1 / 9
10C0-65	65	356	113086	3183	1 / 4

11

- Tube for item 10C0
- Chrome plated



KT NO.	mm	L mm	Applied wrench size		
111946	19	460	24mm, 27mm, 30mm	1050	20
112261	22	610	32mm, 36mm, 41mm	1450	16
112576	24	760	46mm, 50mm, 55mm	2400	6
113086	30	860	60mm, 65mm	2610	4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Spanners](#) category:

Click to view products by [KING TONY](#) manufacturer:

Other Similar products are found below :

[74005](#) [74008](#) [1406504-3](#) [1406504-4](#) [1406504-5](#) [1406504-7](#) [1725859-2](#) [9965](#) [999-16625-001](#) [G70515-18](#) [1055265-1](#) [1055267-1](#) [1-1406504-0](#) [1055787-1](#) [DCH.91.251.PA](#) [TG70-18](#) [TG70](#) [G62748-11](#) [DPH.99.005.2K](#) [DCP.91.045.TN](#) [1055512-1](#) [1055276-1](#) [R282303020](#) [TA-0456](#) [DCA.91.149.0TN](#) [TA-0436](#) [TA-0398](#) [TOL-222901](#) [74_Z-0-0-193](#) [294GB-5069-17-N](#) [74_Z-0-0-2](#) [523200-4](#) [294GB-5070-25-A](#) [74_Z-0-0-79](#) [294GB-5070-17-A](#) [74_Z-0-0-321](#) [TOL-171801](#) [PR23350](#) [1490262-2](#) [9968](#) [AC24VS](#) [80117](#) [DCN.91.149.0TK](#) [BT-A-6010CAGE](#) [R282340000](#) [BT-BS-609WT](#) [BT-A-6000B](#) [R282303000](#) [BT-BS-610R](#) [BT-BS-610RT](#)