

Power Driving

7100Z

- DIN ISO 2351-2

KT NO.	⊕ No.	Overall length (mm)	g	10 / 150
715001Z	PZ1	50	9	10 / 150
715002Z	PZ2	50	11	
715003Z	PZ3	50	12	
717001Z	PZ1	70	11	
717002Z	PZ2	70	15	10 / 120
717003Z	PZ3	70	15	
719001Z	PZ1	90	13	
719002Z	PZ2	90	19	10 / 120
719003Z	PZ3	90	19	

7100U

- For torx head screw
- Tamper-resistant type

KT NO.	⊕ Size	Overall length (mm)	g	10 / 150
715006U	T6H	50	7	10 / 150
715007U	T7H	50	5	
715008U	T8H	50	5	
715009U	T9H	50	5	
715010U	T10H	50	7	
715015U	T15H	50	7	
715020U	T20H	50	7	
715025U	T25H	50	8	
715027U	T27H	50	9	
715030U	T30H	50	9	
715040U	T40H	50	11	
717010U	T10H	70	8	
717015U	T15H	70	8	
717020U	T20H	70	10	
717025U	T25H	70	11	
717027U	T27H	70	13	
717030U	T30H	70	13	
717040U	T40H	70	15	10 / 120
711110U	T10H	110	14	
711115U	T15H	110	14	
711120U	T20H	110	18	
711125U	T25H	110	19	
711127U	T27H	110	24	
711130U	T30H	110	24	
711140U	T40H	110	28	

7100R

KT NO.	⊕ Size	Overall length (mm)	g	10 / 150
715000R	RB0	50	7	10 / 150
715001R	RB1	50	8	
715002R	RB2	50	8	
715003R	RB3	50	8	
717000R	RB0	70	9	
717001R	RB1	70	11	
717002R	RB2	70	13	
717003R	RB3	70	13	

2128PR

- torx head tamper-resistant & L-type holder set

Contents	g	10 / 60
7170U T10H, T15H, T20H, T25H, T27H, T30H, T40H	0.17	10 / 60
158902ERA		

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, phosphate sunk
- Magnetic **1/4"** Hex size shank driver



order unit : one blister card

2138PR

- Hexagon head power bits & L-type holder set

Contents	g	10 / 60
7150H H2, H3, H4, H5, H6, H7, H8	0.24	10 / 60
158902ERA		

7400P

- Short head type

KT NO.	⊕ No.	Overall length (mm)	g	10 / 150
745002P	PH2	50	11	10 / 150
747501P	PH1	75	16	10 / 150
747502P	PH2	75	15	10 / 150
747503P	PH3	75	16	10 / 150
741002P	PH2	100	23	10 / 120
741502P	PH2	150	37	10 / 100
742002P	PH2	200	50	10 / 100
743002P	PH2	300	70	10 / 40
743003P	PH3	300	77	10 / 40

7300P

- Long head type

KT NO.	⊕ No.	Overall length (mm)	g	10 / 150
734501P	PH1	45	9	10 / 150
734502P	PH2	45	9	
734503P	PH3	45	10	
736501P	PH1	65	14	
736502P	PH2	65	14	10 / 120
736503P	PH3	65	14	
731101P	PH1	110	26	
731102P	PH2	110	26	10 / 120
731103P	PH3	110	26	
731502P	PH2	150	32	
731503P	PH3	150	33	



5mm Hex size shank driver order unit : one box

Inset Size: The suggested size is according to the depth of bit holder which a bit is inserted.

7200P

- Long head typed

KT NO.	⊕ No.	Overall length (mm)	g	10 / 100
726502P	PH2	65	8	10 / 100
727502P	PH2	75	10	
721102P	PH2	110	14	



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Screwdrivers, Nut Drivers & Socket Drivers](#) category:

Click to view products by [KING TONY](#) manufacturer:

Other Similar products are found below :

[1406504-2](#) [272012M](#) [271001M](#) [30246](#) [HMM-HH](#) [32024](#) [TL10416](#) [612020B](#) [35-045](#) [6951](#) [83](#) [9977](#) [EMF](#) [99833](#) [RB1](#) [S3166V](#) [X103V](#)
[XTD10TP](#) [X108N](#) [HS7N](#) [HS618N](#) [LN25MMN](#) [HS18N](#) [XST1010N](#) [P4N](#) [R146N](#) [P12SN](#) [R5324N](#) [99764N](#) [P8N](#) [99312N](#) [R3163N](#)
[SX101N](#) [LN22N](#) [XTD10N](#) [9955MMN](#) [995MMN](#) [996MMN](#) [LN25N](#) [THS9N](#) [R3166N](#) [R144N](#) [RB2N](#) [HS10N](#) [99964BPN](#) [HS11N](#) [HS12N](#)
[THS8N](#) [TL12N](#) [LN23BPN](#)