

Farnell Code Nos:



HEALTH AND SAFETY DATA SHEET

13 August 1996

KLINGER SEALEX

1. Identification of the substances/preparation and of the company/undertaking

1.1 SUPPLIER:	Klinger Limited The Klinger Building Wharfedale Road Euroway Trading Estate Bradford BD4 6SG	1.2 MATERIAL: GENERIC NAME:	KLINGER SEALEX EXPANDED PTFE JOINT SEALING TAPE.
1.3 PERSON TO C TELEPHONE FAX NO:	CONTACT: John Middlemiss NO: 01274 688222 01274 688549	MSDS REF: ISSUE DATE: STATE OF ISSUE:	50 10/06/96 B

2. Composition/information on ingredients

INGREDIENT 1:	Polyetrafluoroethylene	100 %	
INGREDIENT 2:			
INGREDIENT 3:			
INGREDIENT 4:			
INGREDIENT 5:			

3. Hazard Identification

In its form as supplied, has no known hazards. Above 260Deg C in number of decomposition products can be produced which represents a health risk if inhaled:- At 440Deg C Carbonyl Fluoride. Never use PTFE products above 360Deg C. Do not smoke when handling PTFE material.

4. First-Aid Measures

SKIN CONTACT:	Wash with soapy water.
EYE CONTACT:	Remove Solid particle(s) and rinse well with water.
INGESTION:	Drink plenty of fluid to assist passage through the system.
INHALATION:	Not applicable normally but if with fumes above 260 Deg C remove to fresh air and seek medical attention.

Klinger Limited The Klinger Building Wharfedale Road Euroway Trading Estate Bradford BD4 6SG Tel (01274) 688222 Fax (01274) 688549 Telex 517036

International Tel +44 1274 688222 Fax +44 1274 688549



Certificate No FM 10571



13 August 1996

KLINGER SEALEX

5. Fire Fighting Measures

EXTINGUISHING MEDIA:	Use Foam, Dry Powder or Carbon Dioxide - Treat as oil free.
SPECIAL FIRE FIGHTING PROCEDURES:	Self contained breathing apparatus should be used and eye protection.
ADDITIONAL ADVICE:	

6. Accidental Release Measures

PERSONAL PRECAUTION:	See point four. Use personal protection equipment.	
ENVIRONMENTAL PRECAUTION:	Do not burn.	
METHOD FOR CLEANING UP:	Use approved vacuum cleaner.	
7. Handling and Storage		

HANDLING:	None required other than no smoking. (See Section 8)
STORAGE:	Avoid sources of heat.

8. Exposure controls/personal protection

OES MEL EH40 93:		
RESPIRATORY PROTECTION: C	Only necessary in fires and at temperature above 260 Deg	
VENTILATION:	No special steps necessary below 260 Deg C	
HAND PROTECTION:		
EYE PROTECTION:		
SKIN PROTECTION:		
OTHERS:	Wear overalls and gloves against cuts and abrasions from protruding metal insert material.	

Klinger Limited The Klinger Building Wharfedale Road Euroway Trading Estate Bradford BD4 6SG Tel (01274) 688222 Fax (01274) 688549 Telex 517036

International Tel +44 1274 688222 Fax +44 1274 688549





13 August 1996

KLINGER SEALEX

9. Physical and chemical properties

APPEARANCE AND ODOUR:	Soft White Tape / No Smell	
BOILING POINT:		
MELTING POINT:	Decomposes	
FLASH POINT:		
FLAMMABILITY:		
AUTOFLAMMABILITY:		
EXPLOSIVE PROPERTIES:	N/A	
OXIDISING PROPERTIES:		
VAPOUR PRESSURE:	N/A	
SPECIFIC GRAVITY:	0.4 -0.6	
SOLUBILITY IN WATER:	Insoluble	
PARTITION COEFFICIENT n-Octanol/Water:		

10. Stability and Reactivity

CONDITIONS TO AVOID:

MATERIAL TO AVOID:

HAZARDOUS DECOMPOSITION PRODUCT:

11. Toxicological Information

Non Toxic at normal temperature

Klinger Limited The Klinger Building Wharfedale Road Euroway Trading Estate Bradford BD4 6SG Tel (01274) 688222 Fax (01274) 688549 Telex 517036

International Tel +44 1274 688222 Fax +44 1274 688549





13 August 1996

KLINGER SEALEX

12. Ecological Information

Not Biodegradable.

ECOTOXITY:

OTHER ADVERSE EFFECTS:

13. Disposal consideration

Should be by burial on approved land-fill site properly licensed. Should not be incinerated.

14. Transport Information

None required other than good materials handling practices.

Klinger Limited The Klinger Building Wharfedale Road Euroway Trading Estate Bradford BD4 6SG Tel (01274) 688222 Fax (01274) 688549 Telex 517036

International Tel +44 1274 688222 Fax +44 1274 688549



Certificate No FM 1057

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for klinger manufacturer:

Other Similar products are found below :

7114898