

- Excellent light dispersion
- Made of PC with increased resistance to weather conditions

#### APPLICATION

- LED protection and light diffusion in lighting fixtures


#### MOUNTING

- Snapped in a dedicated profile

#### ADDITIONAL INFORMATION

- ATTENTION! rigid cover, not intended for bending or deformation
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

#### TECHNICAL DRAWING



#### TECHNICAL SPECIFICATIONS

Finish	satin
Material	PC
Shape	round
Maximum length on request	6000 mm
Light transmission	78 %
Width	30 mm
Possibility of obtaining a line of light	yes

Length	Ref
1000 mm	B17162S_1
2005 mm	B17162S_2
3010 mm	B17162S_3

#### RELATED PROFILES > ARCHITECTURAL



**JAZ**  
A08547

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Lighting Mounting Accessories](#) category:*

*Click to view products by [KLUS](#) manufacturer:*

Other Similar products are found below :

[3SU1900-0AC81-0AA0](#) [3SU1900-0AK10-0AA0](#) [3SU1401-2BB40-3AA0](#) [1SFA616921R2142](#) [A4970001](#) [A4980040](#) [C1900000](#) [C2910001](#)  
[C7980001](#) [E4900001S](#) [E4990001](#) [C1010000S](#) [F7000120S](#) [F7000101](#) [1-2213678-6](#) [89270019](#) [C7940001](#) [F1000116](#) [A2000138](#) [A2000116](#)  
[84000139](#) [H5010001](#) [89000116](#) [A2000139](#) [70330039P020](#) [84000116](#) [70000139](#) [J6999819](#) [V3000139](#) [J6000121](#) [89000138](#) [H5999901](#)  
[89000639](#) [F1999901](#) [63580000](#) [C1999922](#) [76320041S](#) [76000116](#) [J6999902](#) [A00758A07\\_1](#) [AE-WLPR-60P2](#) [PA-GLAX1M-AL-10](#)  
[A05554A\\_1](#) [C24005C10](#) [PA-ZASGLAXMNKK-00](#) [B17013S\\_1](#) [A05556A07\\_1](#) [PA-GLAXMICNK1M-AL](#) [AE-WBCUNI-10DIM](#)  
[C24338C02](#)