Miniature Toggle Switches



Specifications:

250 V AC, 3 A / 125 V AC, 6 A Contact rating:

30 V DC, 4 A / 12 V DC, 5 A

6 V DC, 6 A

 $< 20 \, m\Omega$ Contact resistance:

Insulation resistance: $> 1000 \text{ M}\Omega$ at 500 V DC

Dielectric strength: 1500 V, 50 Hz for the duration of 1 minute

Operating temperature: -45 °C to +140 °C

Mechanical life: minimum 300 000 operations

Contacts: coin silver (common contact copper alloy, silver-plated)

also available gold-plated, version B and G, see page 4

Terminals: solder tags, copper alloy silver-plated

further terminal versions see page 8

Material: case: diallyle-phthalate, meets UL 94 V-0, black

lever: chromium-plated, metal parts: nickel-plated

bushing M 6 x 0.75 with locking plate, key 9 mm Mounting: hand-soldering - max.: 60 W, 3 sec, 420 °C Soldering conditions:

wave-soldering - max.: 5 sec, 270 °C

Accessories:

Knurled nut, nickel-plated

R 675 M 6 x 0,75, Ø 8 mm



Waterproof sealing caps (height 14.3 mm)

black ET 102 ET 108 yellow red ET 109

Waterproof sealing cap with mounting screw

Plastic caps (height 11.5 mm)

orange	C 1103
blue	C 1104
black	C 1105
green	C 1106
grey	C 1107
yellow	C 1108
red	C 1109
white	C 1110





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Bezels / Switch Caps category:

Click to view products by Knitter-Switch manufacturer:

Other Similar products are found below:

896805000 LW1A-B2-R LW2A-B1-G LW2A-B1-S 61-9221.0 61-9221.9 61-9593.0 61-9593.2 61-9600.1 704.604.4 704-6089 704-6097 704.955.3 76 760203000 760503000 766601000 MG12KB MH11 MH13 MH16 MHU31 800C2BLK MJ621 MJ623 MJ626 MJ627 908-1634 92-343.200 92-343.400 95CAP-001 95CAP-010 95CAP-112 11-932.7 99-920.8 A0162J A0163D 11-931.2 11-932.5 11-937 A16ZT-5011B 121160200 AT496F AT496H AW-RF8 161006 1631032 1631034 1631040 1802169