



Specifications:

Contact rating: 500mA, 30V DC
 Contact resistance: 100mOhm max.
 Insulation resistance: 100MOhm min. at 500V DC
 Dielectric strength: 250V AC for 1 minute
 Operating temperature: -20°C to +70°C
 Mechanical life: 300 000 cycles min.
 Operating force: 50gf max.
 Soldering conditions: 260 +/-5°C, 3sec. max.
 Material: Cover / plunger: POM, UL94HB
 Body / lever: PBT, UL94V-0
 Contact: BeCu with silver plated
 Terminals: brass, silver plated

Compliance: RohS II (2011/65/EU)

Tolerances:0.00 to 30.00:±0.20mm 30.01 to 80.00:±0.25mm		Date	Name	<h1>DM-SSM-01C-L2</h1>
		11/05	dr	
Dimensions	08/17	dr		
Travel	08/14	dr		
Rename	07/13	dr		<h2>30 07 27</h2>
Material	12/12	dr		
Revised	03/10	dr		Page
Modifications	Date	Name		1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Basic / Snap Action Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[5SM901-S12](#) [5SM9-S12N195](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM82](#) [6HM89](#) [6SE1](#)
[6SX1-H58](#) [70500216](#) [70599106](#) [MBD5B1](#) [MBH2731](#) [73-316-0012](#) [EXD-AR20](#) [79211923](#) [79218589](#) [7AS12](#)
[MIL30126AB6BBMD4A12XAU](#) [ML-1155](#) [ML-1376](#) [831010C3.0](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [8SX26-H33](#)
[914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#) [11SM1-TN107](#) [11SM405](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SM2442-T](#)
[11SM76-T](#) [11SM77-H58](#) [11SM77-T](#) [11SM863-T](#) [11SM866](#) [A7CN-1M-1-LEFT](#) [A831700C7.0](#) [121EN188-R](#) [1245.0120](#)